

HANDRA Forward - Ø2"





LH5004.595-EN-SLFH-350-740



22 mm
55/64"



40 mm
1 37/64"



[SLFH]

Special linear,
Forward throw

Configuration



Light distribution	[SLFH] 44x46°
Delivered lumens flux	100 lm
Rated input power	1 W
Color temperature	4000 K CRI 70
Luminaire efficacy	100 lm/W
Lamp	1 LED
Color Deviation	4 SDCM
Lifetime L90 (hour)	>102,000
Lifetime L80 (hour)	>102,000

Options

Technical information

Housing	Corrosion resistant, die-cast, marine grade aluminum housing
Finishing	Chromate conversion pretreatment followed by electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Liquid gasket
Lens / Reflector	High reflectance aluminium coating
Glass / Diffusor	Custom Design PMMA Diffusor
Impact protection	IK10
Ingress protection	IP65
Input voltage	3 Vdc (Max) 350 mA
Insulation class	Class III
Weight	0.05 kg
LED module	High power LEDs on metal-core PCB
Driver	External LED driver
Through wiring	Single power cord entry
Operating temperature	-25...50°C
Power cord	8" of flexible power cord
Packing box dimensions	7*7*7 cm
Notes	QUICK SHIP: Some variants will be delivered faster. Please consult the factory.

Accessories (To be ordered separately)

Mounting accessories	Mounting accessories	Mounting accessories
		
DALI & On/Off driver within an IP67 box for 1 to 6 HANDRA modules	DALI & On/Off driver within an IP67 box for 7 to 15 HANDRA modules	DALI & On/Off driver within an IP67 box for 16 to 35 HANDRA modules
007502063	007502064	007502065

Project name					Type		Quantity	
Date			Note					
LH5004.595-EN-SLFH-350-740-__ - __								

Light distribution	Rated input power	Color temperature	Control	Product colors
[SLFH] Special linear, Forward throw - 44x46°	[350] 1 W	[740] 4000 K CRI 70	[ONOFF] On/Off	[HM1]  Black
		[827] 2700 K CRI 80	[DALI] DALI	[HM2]  Dark gray
		[830] 3000 K CRI 80		[HM3]  Anthracite gray
		[840] 4000 K CRI 80		[HM4]  Light gray
				[HM5]  White
				[HM6]  Bronze
				[CC]  Custom color (Please specify RAL code)
Accessories (<i>To be ordered separately</i>)				
Mounting accessories				
[007502063] DALI & On/Off driver within an IP67 box for 1 to 6 HANDRA modules				
[007502064] DALI & On/Off driver within an IP67 box for 7 to 15 HANDRA modules				
[007502065] DALI & On/Off driver within an IP67 box for 16 to 35 HANDRA modules				