

TILA S AFX 2 Module

heper

LL2030.862-US-T4-700-840









[T4] Type IV

Configuration

Light distribution [T4] 117x64° Delivered lumens flux 7255 lm Rated input power 67 W **Color temperature** 4000 K CRI 80 Luminaire efficacy 108 lm/W Lamp 32 LED **Color Deviation** 4 SDCM B1-U0-G1 **BUG** rating >102,000 Lifetime L90 (hour) Lifetime L80 (hour) >102,000

Options

Technical information

Mounting Direct pole or side bracket mountable. Tenon: Ø2 1/4" x 4"

Housing Corrosion resistant, marine grade aluminum

housing

Finishing Chromate conversion pretreatment followed by

electrostatic powder coating

Fasteners Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket Liquid silicone

Lens / Reflector PMMA lens with high optical efficiency
Glass / Diffusor Tempered safety glass

Glass / DiffusorTempered safety glassImpact protectionIK08Ingress protectionIP66

Input voltage120-277V 50/60HzInsulation classClass I

Weight 40.04 lbs (10'), 51.17 lbs (13')
LED module High power LEDs on metal-core PCB

DriverInternal LED driverThrough wiringSingle power cord entryOperating-40...50°C

Operating temperature


Power cord20" of outdoor use rated flexible power cordPole detailPoles are supplied with flange plate. Flange

cover and anchorage can be ordered separately.

Embedded base is optional

and applicable standards.

Product specific poles with base plate



Project name					Туре	Quantity	
Date			Note				

LL2030.862-US-T4-700-840-__--_--

Light distribution	Rated input power	Color temperature	Control	Product colors
[T4] Type IV - 117x64°	[700] 67 W	[840] 4000 K CRI 80	[ONOFF] On/Off	[HM1] Black
[P4] Pedestrian crosswalk distribution - 20x78° [T1] Type I - 111x48° [T2] Type II - 133x48° [T2] Type II - 149x54° [T3] Type III - 143x63° [T5] Type V - 117°	[350] 34 W [500] 48 W	[827] 2700 K CRI 80 [830] 3000 K CRI 80 [740] 4000 K CRI 70	[0-10V] 0-10V	[HM2] Dark gray [HM3] Anthracite gray [HM4] Light gray [HM5] White [HM6] Bronze
Height [H3] 10' [H4] 13.1'	Extras Luminaire body options [DPC] Double powder coating			custom color (Please specify RAL code)