



LR9003.530-US-ASYM-20x65-350-740-ONOFF



[EL]
Elliptical

Configuration

Light distribution	[EL] 40°
Delivered lumens flux	650 lm
Rated input power	6 W
Color temperature	4000 K CRI 70
Luminaire efficacy	108 lm/W
Lamp	4 LED
Color Deviation	3 SDCM
Lifetime L90 (hour)	>145,000
Lifetime L80 (hour)	>145,000


Options

Technical information

Housing	Corrosion resistant, die-cast, marine grade aluminum housing
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone
Lens / Reflector	PMMA lens with high optical efficiency
Glass / Diffusor	Tempered safety glass
Impact protection	IK08
Ingress protection	IP67
Input voltage	120-277V 50/60Hz
Insulation class	Class I
Weight	4 lbs
LED module	High power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge protection	3/3 kV
Power factor	> 0.40
Through wiring	Single power cord entry
Operating temperature	-40...50°C
Power cord	12" of rubber-sheathed power cord

Accessories (Included)

Mounting accessories



Plastic sleeve for
WEDGE

160401047/6

Accessories (To be ordered separately)









Mounting accessories



Case removing
vacuum

160404012

Project name					Type		Quantity	
Date			Note					
LR9003.530-US-ASYM-20x65-350-740-ONOFF-__								

Light distribution	Rated input power	Color temperature	Control	Product colors	
[EL] Elliptical - 40°	[350] 6 W	[740] 4000 K CRI 70	[ONOFF] On/Off	[HM1] Black	
[VN] Very narrow - NEMA Type 1 - 10°		[830] 3000 K CRI 80		[HM2] Dark gray	
				[HM3] Anthracite gray	
				[HM4] Light gray	
				[HM5] White	
				[HM6] Bronze	
				[9006] White aluminium (RAL 9006)	
				[CC] Custom color (Please specify RAL code)	
Accessories <i>(Included)</i>	Accessories <i>(To be ordered separately)</i>				
Mounting accessories	Mounting accessories				
[160401047/6] Plastic sleeve for WEDGE	[160404012] Case removing vacuum				