
WEDGE


CE UK IKO8 IP67





LR9003.531-EN-VN-350-740-ONOFF-EN-C1







Very narrow

Variant

Light distribution [VN] 10° **Delivered lumens flux** 594 lm Rated input power 6 W **Colour temperature** 4000 K CRI 70 **Luminaire efficacy** 99 lm/W 4 LED Lamp MacAdam Ellipse 3 SDCM Lifetime L90B50 (hour) >145,000 >145,000 Lifetime L80B50 (hour)

Options

Technical information

Housing	Corrosion resistant, die-cast, marine grade		
	aluminum housing		
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)		
Gasket	Silicone		
Lens / Reflector	PMMA lens with high optical efficiency		
Glass / Diffusor	Tempered safety glass		
Impact protection	IK08		
Ingress protection	IP67		
Input voltage	220-240V 50/60Hz		
Insulation class	Class I		
Weight	1.9 kg		
LED module	High power LEDs on metal-core PCB		
Driver	Internal LED driver		
Driver surge	3/3 kV		
protection			
Power factor	> 0.40		
Through wiring	Single cable entry		
Operating	-4050°C		
temperature			
Cable	0.3 m of rubber-sheated cable		

Mounting accessories



Plastic sleeve for WEDGE

160401047/6



Case removing vacuum

160404012

Mounting accessories Mounting accessories



Connector set - 5pole

141407400

Project name			Туре	Quantity		
Date			Note			

LR9003.531-EN-VN-350-740-ONOFF-EN-C1-__-

Light distribution	Rated input power	Colour temperature	Control	Product colours
[VN] Very narrow - 10°	[350] 6 W	[740] 4000 K CRI 70	[ONOFF] On/Off	[HM1] Black
[EL] Elliptical - 20x65°		[830] 3000 K CRI 80		[HM2] Dark grey
				[HM3] Anthracite grey
				[HM4] Light grey
				[HM5] White
				[HM6] Bronze
				[9006] White aluminium (RAL 9006)
				Custom colour (Please specify RAL code)
Extras	Accessories (Included)	Accessories (To be ordered separately)		
Consult the factory	Mounting accessories	Mounting accessories		
[UNI] 120-277V 50/60Hz	[160401047/6] Plastic sleeve for WEDGE	[160404012] Case removing vacuum		
		[141407400] Connector set - 5-pole		