
WEDGE


CE UK IKO8 IP67





LR9003.531-EN-VN-350-830-ONOFF-EN-C1







Very narrow

Variant

Light distribution [VN] 10° **Delivered lumens flux** 502 lm Rated input power 6 W **Colour temperature** 3000 K CRI 80 **Luminaire efficacy** 84 lm/W 4 LED Lamp MacAdam Ellipse 3 SDCM Lifetime L90B50 (hour) >145,000 >145,000 Lifetime L80B50 (hour)

Options

Technical information

Housing	Corrosion resistant, die-cast, marine grade
	aluminum housing
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone
Lens / Reflector	PMMA lens with high optical efficiency
Glass / Diffusor	Tempered safety glass
Impact protection	IK08
Ingress protection	IP67
Input voltage	220-240V 50/60Hz
Insulation class	Class I
Weight	1.9 kg
LED module	High power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge	3/3 kV
protection	
Power factor	> 0.40
Through wiring	Single cable entry
Operating	-4050°C
temperature	
Cable	0.3 m of rubber-sheated cable

Mounting accessories



Plastic sleeve for WEDGE

160401047/6



Case removing vacuum

160404012

Mounting accessories Mounting accessories



Connector set - 5pole

141407400

Project name		Туре	Quantity				
Date			Note				

LR9003.531-EN-VN-350-830-ONOFF-EN-C1-__-

Light distribution	Rated input power	Colour temperature	Control	Product colours
[VN] Very narrow - 10°	[350] 6 W	[830] 3000 K CRI 80	[ONOFF] On/Off	[HM1] Black
[EL] Elliptical - 20x65°		[740] 4000 K CRI 70		[HM2] Dark grey
				[HM3] Anthracite grey
				[HM4] Light grey
				[HM5] White
				[HM6] Bronze
				[9006] White aluminium (RA 9006)
				[CC] Custom colour (Pleas specify RAL code)
Extras	Accessories (Included)	Accessories (To be ordered separately)		I
Consult the factory	Mounting accessories	Mounting accessories		
[UNI] 120-277V 50/60Hz	[160401047/6] Plastic sleeve for WEDGE	[160404012] Case removing vacuum	_	
		[141407400] Connector set - 5-pole		