

WINGS AFX 2 Module

LL2012.862-EN-T2-350-840-ONOFF









[T2] Type II

Configuration

Light distribution [T2] 133x48° Delivered lumens flux 3955 lm Rated input power 34 W **Color temperature** 4000 K CRI 80 Luminaire efficacy 116 lm/W Lamp 32 LED **Color Deviation** 4 SDCM B1-U1-G0 **BUG** rating Lifetime L90 (hour) >102,000 Lifetime L80 (hour) >102,000

Options

Technical information

Mounting Surface mountable Housing Corrosion resistant, marine grade aluminum housing Finishing Chromate conversion pretreatment followed by electrostatic powder coating Fasteners Stainless steel (AISI 304 / EN 1.4301 grade) Gasket Liquid silicone Lens / Reflector PMMA lens with high optical efficiency Glass / Diffusor Tempered safety glass Impact protection Ingress protection IP66 Input voltage 220-240V 50/60Hz **Insulation class** Class I 50.2 kg (3 m), 57.24 kg (4 m) Weight High power LEDs on metal-core PCB LED module Driver Internal LED driver **Driver surge** 10/6 kV

protection **Power factor** > 0.95 Through wiring Single power cord entry Operating -40...50°C

temperature

Power cord 20" of outdoor use rated flexible power cord Packing box

45*8*58 cm

dimensions

Pole detail Poles are supplied with flange plate. Flange

cover and anchorage can be ordered separately.

Embedded base is optional

and applicable standards.

Product specific poles with base plate

	Configuration code I	Height	Diameter / Dimensions	Spigot / End diameter
	PAFD.R01.T002-H3	10'	7.3x4.7"	
1	PAFD.R01.T002-H4	13.1'	7.3x4.7"	

Project na	me		Туре	Quantity	
Date		Note			

LL2012.862-EN-T2-350-840-ONOFF-__--_--

Light distribution	Rated input power	Color temperature	Control	Product colors
[T2] Type II - 133x48°	[350] 34 W	[840] 4000 K CRI 80	[ONOFF] On/Off	[HM1] Black
[P4] Pedestrian crosswalk distribution - 20x78°	[500] 48 W	[827] 2700 K CRI 80		[HM2] Dark gray
[T1] Type I - 111x48°	[700] 67 W	[830] 3000 K CRI 80 [740] 4000 K CRI 70		[HM3] Anthracite gray
[T2] Type II - 149x54°				[HM4] Light gray
[T3] Type III - 143x63°				[HM5] White
[T4] Type IV - 117x64°				[HM6] Bronze
[T5] Type V - 117°				Custom color (Please specify RAL code)
Height	Extras			
[H3]	Consult the factory			
10' [H4] 13.1' [HC]	[UNI] 120-277V 50/60Hz			
	Luminaire body options			
	[DPC] Double powder coating			