

### **WEDGE**

# heper "

#### LR9003.531-US-VN-350-740-ONOFF







[VN]
Very narrow - NEMA
Type 1

#### Configuration

**Light distribution** [VN] 10° Delivered lumens flux 594 lm Rated input power 6 W **Color temperature** 4000 K CRI 70 99 lm/W **Luminaire efficacy** 4 LED Lamp **Color Deviation** 3 SDCM Lifetime L90 (hour) >145,000 >145,000 Lifetime L80 (hour)

#### Options

#### Technical information

Housing Corrosion resistant, die-cast, marine grade aluminum housing Fasteners Stainless steel (AISI 304 / EN 1.4301 grade) Gasket Silicone Lens / Reflector PMMA lens with high optical efficiency Glass / Diffusor Tempered safety glass Impact protection IK08 **Ingress protection** IP67 Input voltage 120-277V 50/60Hz **Insulation class** Class I Weight 4 lbs **LED** module High power LEDs on metal-core PCB Internal LED driver Driver 3/3 kV **Driver surge** protection **Power factor** > 0.40 Through wiring Single power cord entry Operating -40...50°C temperature Power cord 12" of rubber-sheated power cord

and applicable standards.

Mounting accessories



Plastic sleeve for WEDGE

160401047/6

Mounting accessories



Case removing vacuum

160404012

Project name					Туре	Quantity	
Date			Note				

## LR9003.531-US-VN-350-740-ONOFF-\_\_

Light distribution	Rated input power	Color temperature	Control	Product colors
<b>[VN]</b> Very narrow - NEMA Type 1 - 10°	[ <b>350]</b> 6 W	[ <b>740]</b> 4000 K CRI 70	[ONOFF] On/Off	[HM1] Black
[EL] Elliptical - 40°		[ <b>830]</b> 3000 K CRI 80		[HM2] Dark gray
Emptical 40				[HM3] Anthracite gray
				[HM4] Light gray
				[HM5] White
				[HM6] Bronze
				[9006] White aluminium (RA 9006)
				[CC] Custom color (Please specify RAL code)
Accessories (Included)	Accessories (To be ordered separately)			
Mounting accessories	Mounting accessories			
[160401047/6] Plastic sleeve for WEDGE	[160404012] Case removing vacuum			