

WINGS AFX 2 Module

LL2012.862-EN-T4-350-827-ONOFF









Type IV

Configuration

Light distribution [T4] 117x64° Delivered lumens flux 3940 lm Rated input power 34 W **Color temperature** 2700 K CRI 80 Luminaire efficacy 116 lm/W Lamp 32 LED **Color Deviation** 3 SDCM B1-U0-G1 **BUG** rating Lifetime L90 (hour) >102,000 Lifetime L80 (hour) >102,000

Options

dimensions

Technical information

Mounting Surface mountable Housing Corrosion resistant, marine grade aluminum housing Finishing Chromate conversion pretreatment followed by electrostatic powder coating Fasteners Stainless steel (AISI 304 / EN 1.4301 grade) Gasket Liquid silicone Lens / Reflector PMMA lens with high optical efficiency Glass / Diffusor Tempered safety glass

Impact protection Ingress protection IP66 Input voltage 220-240V 50/60Hz **Insulation class** Class I 50.2 kg (3 m), 57.24 kg (4 m)

Weight High power LEDs on metal-core PCB LED module Driver Internal LED driver

Driver surge 10/6 kV

protection

Power factor > 0.95 Through wiring Single power cord entry

Operating -40...50°C temperature

Power cord 20" of outdoor use rated flexible power cord

Packing box 45*8*58 cm

Pole detail Poles are supplied with flange plate. Flange

> cover and anchorage can be ordered separately. Embedded base is optional

Product specific poles with base plate

	Configuration code I	Height	Diameter / Dimensions	Spigot / End diameter
	PAFD.R01.T002-H3	10'	7.3x4.7"	
I	PAFD.R01.T002-H4	13.1'	7.3x4.7"	

Project na	me		Туре	Quantity	
Date		Note			

LL2012.862-EN-T4-350-827-ONOFF-__--_--

Light distribution	Rated input power	Color temperature	Control	Product colors
[T4] Type IV - 117x64°	[350] 34 W	[827] 2700 K CRI 80	[ONOFF] On/Off	[HM1] Black
[P4] Pedestrian crosswalk distribution - 20x78°	[500] 48 W	[830] 3000 K CRI 80		[HM2] Dark gray
[T1] Type I - 111x48°	[700] 67 W	[740] 4000 K CRI 70 [840] 4000 K CRI 80		[HM3] Anthracite gray
[T2] Type II - 133x48°				[HM4] Light gray
[T2] Type II - 149x54°				[HM5] White
[T3] Type III - 143x63°				[HM6] Bronze
[T5] Type V - 117°				[CC] Custom color (Please specify RAL code)
Height	Extras			
[H3]	Consult the factory			
10' [H4] 13.1' [HC]	[UNI] 120-277V 50/60Hz			
	Luminaire body options			
	[DPC] Double powder coating			