

WINGS AFX 2 Module

LL2012.862-EN-T4-700-840-ONOFF









Type IV

Configuration

Light distribution [T4] 117x64° Delivered lumens flux 7275 lm Rated input power 67 W **Color temperature** 4000 K CRI 80 Luminaire efficacy 108 lm/W Lamp 32 LED **Color Deviation** 4 SDCM B1-U0-G1 **BUG** rating Lifetime L90 (hour) >102,000 Lifetime L80 (hour) >102,000

Options

Technical information

Mounting Surface mountable Housing Corrosion resistant, marine grade aluminum housing Finishing Chromate conversion pretreatment followed by electrostatic powder coating Fasteners Stainless steel (AISI 304 / EN 1.4301 grade) Gasket Liquid silicone

Lens / Reflector PMMA lens with high optical efficiency Glass / Diffusor Tempered safety glass Impact protection Ingress protection IP66 Input voltage 220-240V 50/60Hz

Insulation class Class I 50.2 kg (3 m), 57.24 kg (4 m) Weight High power LEDs on metal-core PCB LED module Driver Internal LED driver

Driver surge 10/6 kV

protection **Power factor** > 0.95 Through wiring Single power cord entry

Operating -40...50°C

temperature Power cord 20" of outdoor use rated flexible power cord Packing box 45*8*58 cm

dimensions

Pole detail Poles are supplied with flange plate. Flange

cover and anchorage can be ordered separately.

Embedded base is optional

and applicable standards.

Product specific poles with base plate

	Configuration code I	Height	Diameter / Dimensions	Spigot / End diameter	
	PAFD.R01.T002-H3	10'	7.3x4.7"		
1	PAFD.R01.T002-H4	13.1'	7.3x4.7"		

Project na	me		Туре	Quantity	
Date		Note			

LL2012.862-EN-T4-700-840-ONOFF-__--_--

Light distribution	Rated input power	Color temperature	Control	Product colors
[T4] Type IV - 117x64°	[700] 67 W	[840] 4000 K CRI 80	[ONOFF] On/Off	[HM1] Black
[P4] Pedestrian crosswalk distribution - 20x78°	[350] 34 W	[827] 2700 K CRI 80		[HM2] Dark gray
[T1] Type I - 111x48°	[500] 48 W	[830] 3000 K CRI 80 [740] 4000 K CRI 70		[HM3] Anthracite gray
[T2] Type II - 133x48°				[HM4] Light gray
[T2] Type II - 149x54°				[HM5] White
[T3] Type III - 143x63°				[HM6] Bronze
[T5] Type V - 117°				Custom color (Please specify RAL code)
Height	Extras			
[H3]	Consult the factory			
10' [H4] 13.1' [HC]	[UNI] 120-277V 50/60Hz			
	Luminaire body options			
	[DPC] Double powder coating			