

WINGS AFX 2 Module

LL2012.862-US-T3-700-740-ONOFF









Type III

Configuration

Light distribution [T3] 143x63° Delivered lumens flux 8295 lm Rated input power 67 W **Color temperature** 4000 K CRI 70 Luminaire efficacy 123 lm/W Lamp 32 LED **Color Deviation** 4 SDCM B2-U0-G1 **BUG** rating Lifetime L90 (hour) >102,000 Lifetime L80 (hour) >102,000

Options

Technical information

Mounting Surface mountable Housing Corrosion resistant, marine grade aluminum housing Finishing Chromate conversion pretreatment followed by electrostatic powder coating Fasteners Stainless steel (AISI 304 / EN 1.4301 grade) Gasket Liquid silicone Lens / Reflector PMMA lens with high optical efficiency

Glass / Diffusor Tempered safety glass Impact protection Ingress protection IP66 Input voltage 120-277V 50/60Hz

Insulation class Class I 110.44 lbs (10'), 125.92 lbs (13') Weight High power LEDs on metal-core PCB LED module Driver Internal LED driver

Through wiring Single power cord entry Operating -40...50°C

temperature

Power cord 20" of outdoor use rated flexible power cord Packing box 17 23/32"*3 5/32"*22 53/64"

dimensions Pole detail

Poles are supplied with flange plate. Flange

cover and anchorage can be ordered separately.

Embedded base is optional

Product specific poles with base plate

	Configuration code I	Height	Diameter / Dimensions	Spigot / End diameter
	PAFD.R01.T002-H3	10'	7.3x4.7"	
I	PAFD.R01.T002-H4	13.1'	7.3x4.7"	

Project na	me		Туре	Quantity	
Date		Note			

LL2012.862-US-T3-700-740-ONOFF-__--_-

Light distribution	Rated input power	Color temperature	Control	Product colors
[T3] Type III - 143x63°	[700] 67 W	[740] 4000 K CRI 70	[ONOFF] On/Off	[HM1] Black
[P4] Pedestrian crosswalk distribution - 20x78° [T1] Type I - 111x48° [T2] Type II - 133x48° [T2] Type II - 149x54° [T4] Type IV - 117x64° [T5] Type V - 117°	[350] 34 W [500] 48 W	[827] 2700 K CRI 80 [830] 3000 K CRI 80 [840] 4000 K CRI 80		[HM2] Dark gray [HM3] Anthracite gray [HM4] Light gray [HM5] White [HM6] Bronze [CC] Custom color (Please specify RAL code)
Height [H3] 10' [H4] 13.1' [HC]	Extras Luminaire body options [DPC] Double powder coating			