


# LR9012.584-EN-WW-350-830-EN-C1-SS









Wall-wash

Variant

СЕ ЦКА ІКОВ ІР67 →

Light distribution	[WW] 45x85°
Delivered lumens flux	2463 lm
Rated input power	30 W
Colour temperature	3000 K CRI 80
Luminaire efficacy	82 lm/W
Lamp	12 LED
MacAdam Ellipse	3 SDCM
Lifetime L90B50 (hour)	>42,000
Lifetime L80B50 (hour)	>42,000

## Options

Cable

## Technical information

Mounting	Ground recessed mountable
Housing	Corrosion resistant stainless steel housing (AISI
liousing	316L / EN 1.4571 grade)
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone
Lens / Reflector	High reflectance aluminium coating,
	multifaceted micro reflector
Glass / Diffusor	Tempered safety glass
Impact protection	IK08
Ingress protection	IP67
Input voltage	220-240V 50/60Hz
Insulation class	Class I
Weight	7.88 kg
LED module	High power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge	4/4 kV
protection	
Power factor	> 0.97
Through wiring	Single cable entry
Operating	-4050°C
temperature	

0.3 m of rubber-sheated cable

## HPR Pazarlama A.Ş.

Başkent OSB 22. Cd. No: 2, Malıköy, Temelli, Sincan, 06909 Ankara, Turkey +90 312 267 54 30 info@hepergroup.com

#### HEPER Europe GmbH

Ahornweg 5a, 58675 Hemer, Germany +49 237 2901 2975 infoEU@hepergroup.com We reserve the right to change specifications without prior written notice. Edition: 17.05.2024. For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

1/3

# Accessories (Included)

# Accessories (To be ordered separately)

## Mounting accessories



Aluminium case for ZETA 12 Dyno / MOLTO 6 Hybrid

007500402

## Mounting accessories Mounting

Mounting accessories Mounting accessories





Case removing Connector set - 5pole 160404012 141407400 0000

Junction Box 141901135

HPR Pazarlama A.Ş. Başkent OSB 22. Cd. No: 2, Malıköy, Temelli, Sincan, 06909 Ankara, Turkey +90 312 267 54 30 info@hepergroup.com

#### HEPER Europe GmbH

Ahornweg 5a, 58675 Hemer, Germany +49 237 2901 2975 infoEU@hepergroup.com We reserve the right to change specifications without prior written notice. Edition: 17.05.2024. For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

2/3

Project na	me				Туре	Quantity	
Date			Note				
LR9012.	584-EN-W	/W-350-8	30EN	-C1-SS			

<b>[350]</b> 30 W	<b>[830]</b> 3000 K CRI 80	[ONOFF]	[SS]
		On/Off	Stainless steel
	<b>[827]</b> 2700 K CRI 80	<b>[DALI]</b> DALI	
	<b>[740]</b> 4000 K CRI 70		
	<b>[840]</b> 4000 K CRI 80		
Accessories ( <i>To be</i> ordered separately)			
Mounting accessories			
[160404012] Case removing vacuum			
Connector set - 5-pole			
<b>[141901135]</b> Junction Box			
	ordered separately) Mounting accessories [160404012] Case removing vacuum [141407400] Connector set - 5-pole [141901135]	4000 K CRI 70[840]4000 K CRI 80Accessories (To be ordered separately)Mounting accessories[160404012] Case removing vacuum[141407400] Connector set - 5-pole[141901135]	4000 K CRI 70         [840]         4000 K CRI 80    Accessories (To be ordered separately)          Mounting accessories         [160404012]         Case removing vacuum         [141407400]         Connector set - 5-pole         [141901135]

## HEPER Europe GmbH

Ahornweg 5a, 58675 Hemer, Germany +49 237 2901 2975 infoEU@hepergroup.com We reserve the right to change specifications without prior written notice. Edition: 17.05.2024. For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.