


# **ZETA 12 Dyno**

#### LR9012.584-EN-WW-350-830-SS









### Configuration

**Light distribution** [WW] 45x85° Delivered lumens flux 2463 lm Rated input power 30 W **Color temperature** 3000 K CRI 80 **Luminaire efficacy** 82 lm/W Lamp 12 LED **Color Deviation** 3 SDCM Lifetime L90 (hour) >42,000 >42,000 Lifetime L80 (hour)

# Options

#### Technical information

Mounting Ground recessed mountable Housing Corrosion resistant stainless steel housing (AISI 316L / EN 1.4571 grade) **Fasteners** Stainless steel (AISI 304 / EN 1.4301 grade) Gasket Silicone Lens / Reflector High reflectance aluminium coating, multifaceted micro reflector Glass / Diffusor Tempered safety glass Impact protection IK08 IP67 Ingress protection Input voltage 220-240V 50/60Hz **Insulation class** Class I Weight 7.88 kg **LED** module High power LEDs on metal-core PCB Internal LED driver Driver 4/4 kV **Driver surge** protection Power factor > 0.97 Through wiring Single power cord entry

Operating -40...50°C temperature

Power cord 12" of rubber-sheated power cord

and applicable standards.

Mounting accessories



Aluminium case for ZETA 12 Dyno / MOLTO 6 Hybrid

007500402

Mounting accessories Mounting accessories Mounting accessories



Case removing vacuum

160404012

Connector set - 5pole

141407400



Junction Box

141901135

Project na	me			Туре	Quantity	
Date			Note			

## LR9012.584-EN-WW-350-830-\_\_--SS

ight distribution	Rated input power	Color temperature	Control	Product colors
<b>//W]</b> Vall-wash - 45x85°	[ <b>350</b> ] 30 W	[830] 3000 K CRI 80	[ONOFF] On/Off	[SS] Stainless steel
		[ <b>827]</b> 2700 K CRI 80	[ <b>DALI</b> ] DALI	
		[ <b>740</b> ] 4000 K CRI 70		
		[840] 4000 K CRI 80		
ccessories Included)	Accessories (To be ordered separately)			
lounting ccessories	Mounting accessories			
007500402] luminium case for ETA 12 Dyno /	[160404012] Case removing vacuum			
1OLTO 6 Hybrid	[141407400] Connector set - 5-pole			
	[141901135] Junction Box			