





LR9012.584-US-WW-350-740-UNI-C1-SS







Variant

Light distribution [WW] 45x85° **Delivered lumens flux** 2799 lm Rated input power 30 W **Colour temperature** 4000 K CRI 70 **Luminaire efficacy** 93 lm/W Lamp 12 LED MacAdam Ellipse 3 SDCM Lifetime L90B50 (hour) >42,000 >42,000 Lifetime L80B50 (hour)

Options

temperature Cable

Technical information

recrimed inform	ation
Mounting	Ground recessed mountable
Housing	Corrosion resistant stainless steel housing (AISI
	316L / EN 1.4571 grade)
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone
Lens / Reflector	High reflectance aluminium coating,
	multifaceted micro reflector
Glass / Diffusor	Tempered safety glass
Impact protection	IK08
Ingress protection	IP67
Input voltage	120-277V 50/60Hz
Insulation class	Class I
Weight	17.3 lbs
LED module	High power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge	4/4 kV
protection	
Power factor	> 0.97
Through wiring	Single cable entry
Operating	-4050°C

Wall-wash

0.3 m of rubber-sheated cable

Mounting accessories Mounting accessories





Aluminium case for ZETA 12 Dyno / MOLTO 6 Hybrid

Connector set - 5pole

007500402

141407400

Mounting accessories



Case removing vacuum

160404012

Project na	me		Туре	Quantity	
Date		Note			

LR9012.584-US-WW-350-740-___-UNI-C1-SS

Light distribution	Rated input power	Colour temperature	Control	Product colours
[WW] Wall-wash - 45x85°	[350] 30 W	[740] 4000 K CRI 70	[ONOFF] On/Off	[SS] Stainless steel
		[827] 2700 K CRI 80	[0-10V] 0-10V	
		[830] 3000 K CRI 80		
		[840] 4000 K CRI 80		
Accessories (Included)	Accessories (To be ordered separately)			
Mounting accessories	Mounting accessories			
[007500402] Aluminium case for ZETA 12 Dyno / MOLTO 6 Hybrid	[160404012] Case removing vacuum			
[141407400] Connector set - 5-pole				