






LR9012.584-US-WW-350-740-UNI-C1-SS









Variant

Light distribution [WW] 45x85° Delivered lumens flux 2799 lm Rated input power 30 W **Colour temperature** 4000 K CRI 70 Luminaire efficacy 93 lm/W Lamp 12 LED MacAdam Ellipse 3 SDCM >42,000 Lifetime L90B50 (hour) Lifetime L80B50 (hour) >42,000

Options

Technical information

Mounting Ground recessed mountable Corrosion resistant stainless steel housing (AISI Housing 316L / EN 1.4571 grade) **Fasteners** Stainless steel (AISI 304 / EN 1.4301 grade) Gasket Silicone Lens / Reflector High reflectance aluminium coating, multifaceted micro reflector Glass / Diffusor Tempered safety glass IK08 Impact protection Ingress protection IP67 Input voltage 120-277V 50/60Hz **Insulation class** Class I Weight 17.3 lbs High power LEDs on metal-core PCB **LED** module Internal LED driver Driver 4/4 kV **Driver surge** protection Power factor > 0.97 Through wiring Single cable entry Operating -40...50°C

temperature

Cable 0.3 m of rubber-sheated cable

Mounting accessories Mounting accessories





Aluminium case for ZETA 12 Dyno / MOLTO 6 Hybrid

Connector set - 5pole

007500402

141407400

Mounting accessories



Case removing vacuum

160404012

Project name					Туре	Quantity	
Date			Note				

LR9012.584-US-WW-350-740-___-UNI-C1-SS

Light distribution	Rated input power	Colour temperature	Control	Product colours	
[WW] Wall-wash - 45x85°	[350] 30 W	[740] 4000 K CRI 70	[ONOFF] On/Off	[SS] Stainless steel	
		[827] 2700 K CRI 80	[0-10V] 0-10V		
		[830] 3000 K CRI 80			
		[840] 4000 K CRI 80			
Accessories (Included)	Accessories (To be ordered separately)				
Mounting accessories	Mounting accessories				
[007500402] Aluminium case for ZETA 12 Dyno / MOLTO 6 Hybrid	[160404012] Case removing vacuum				
[141407400] Connector set - 5-pole					