ZEROX S Hybrid


heper

LR9016.693-US-S-700-830-SS











[S] Spot - NEMA Type 0

Configuration

Light distribution [S] 7° **Delivered lumens flux** 849 lm 10 W Rated input power **Color temperature** 3000 K CRI 80 84 lm/W **Luminaire efficacy** 1 LED Lamp 5 SDCM **Color Deviation** Lifetime L90 (hour) >72,600 Lifetime L80 (hour) >72,600

Options

Technical information

Mounting	Ground recessed mountable
Housing	Corrosion resistant stainless steel housing (AISI
	316L / EN 1.4571 grade)
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone
Lens / Reflector	High reflectance aluminium coating
Glass / Diffusor	Tempered safety glass
Impact protection	IK10
Ingress protection	IP67
Input voltage	120-277V 50/60Hz
Insulation class	Class I
Weight	6.1 lbs
LED module	Multi-chip high power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge	2/2 kV
protection	
Power factor	> 0.90
Through wiring	Single power cord entry

Operating temperature

Power cord 12" of rubber-sheated power cord

and applicable standards.

-30...50°C

Mounting accessories



Connector set - 5pole

141407400



Case removing vacuum

160404012

Mounting accessories Mounting accessories



Plastic case for **ZEROX S**

007502091

Project na	me		Туре	Quantity	
Date		Note			

LR9016.693-US-S-700-830-___-SS

Light distribution	Rated input power	Color temperature	Control	Product colors
[S] Spot - NEMA Type 0 -	[700] 10 W	[830] 3000 K CRI 80	[ONOFF] On/Off	[SS] Stainless steel
7° [N] Narrow - NEMA Type 2 - 26°	[350] 5 W	[827] 2700 K CRI 80	[0-10V] 0-10V	
	[500] 6 W	[740] 4000 K CRI 70		
		[840] 4000 K CRI 80		
Accessories (Included)	Accessories (To be ordered separately)			
Mounting accessories	Mounting accessories			
[141407400] Connector set - 5-pole	[160404012] Case removing vacuum			
	[007502091] Plastic case for ZEROX S			