ZEROX M Hybrid











LR9017.690-EN-S-700-740-EN-C1-SS











Spot

Variant

Light distribution [S] 7° **Delivered lumens flux** 2038 lm Rated input power 18 W **Colour temperature** 4000 K CRI 70 **Luminaire efficacy** 113 lm/W Lamp 2 LED MacAdam Ellipse 5 SDCM Lifetime L90B50 (hour) >72,600 Lifetime L80B50 (hour) >72,600

Options

Technical information

Mounting	Ground recessed mountable
Housing	Corrosion resistant stainless steel housing (AISI
	316L / EN 1.4571 grade)
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone
Lens / Reflector	High reflectance aluminium coating
Glass / Diffusor	Tempered safety glass
Impact protection	IK10
Ingress protection	IP67
Input voltage	220-240V 50/60Hz
Insulation class	Class I
Weight	4.06 kg
LED module	Multi-chip high power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge	1/1 kV
protection	
Power factor	> 0.90

Operating temperature

Through wiring

Cable 0.3 m of rubber-sheated cable

Başkent OSB 22. Cd. No: 2, Malıköy, Temelli, Sincan, 06909 Ankara, Turkey +90 312 267 54 30 info@hepergroup.com Ahornweg 5a, 58675 Hemer, Germany +49 237 2901 2975 infoEU@hepergroup.com Single cable entry

-30...50°C

Accessories (To be ordered separately)

Mounting accessories Mounting accessories Mounting accessories









Case removing vacuum

Connector set - 5pole

Junction Box

160404012

141407400

141901135

Mounting accessories



Plastic case for **ZEROX M**

007502092

Project na	me		Туре	Quantity	
Date		Note			

LR9017.690-EN-S-700-740-___-EN-C1-SS-___

[700] 18 W [350] 10 W [500] 13 W	[740] 4000 K CRI 70 [827] 2700 K CRI 80 [830] 3000 K CRI 80 [840] 4000 K CRI 80	[ONOFF] On/Off [DALI] DALI	[SS] Stainless steel
10 W [500] 13 W	2700 K CRI 80 [830] 3000 K CRI 80 [840]		
13 W	3000 K CRI 80 [840]		
Assessavies (To be			
Association (To be			1
ordered separately)			
Mounting			
accessories	-		
[160404012] Case removing vacuum			
[141407400] Connector set - 5-pole			
[141901135] Junction Box			
[007502092] Plastic case for ZEROX M			
	Case removing vacuum 141407400] Connector set - 5-pole 141901135] unction Box 007502092] Plastic case for ZEROX	160404012] Case removing vacuum 141407400] Connector set - 5-pole 141901135] unction Box 007502092] Plastic case for ZEROX	160404012] Case removing vacuum 141407400] Connector set - 5-pole 141901135] unction Box 007502092] Plastic case for ZEROX