
ZEROX M Hybrid


heper "

LR9017.690-EN-S-700-830-SS











[S] Spot - NEMA Type 0

Configuration

Light distribution [S] 7° Delivered lumens flux 1888 lm Rated input power 18 W **Color temperature** 3000 K CRI 80 104 lm/W **Luminaire efficacy** Lamp 2 LED **Color Deviation** 5 SDCM Lifetime L90 (hour) >72,600 Lifetime L80 (hour) >72,600

Options

Technical information

Mounting Ground recessed mountable Housing Corrosion resistant stainless steel housing (AISI 316L / EN 1.4571 grade) **Fasteners** Stainless steel (AISI 304 / EN 1.4301 grade) Gasket Silicone Lens / Reflector High reflectance aluminium coating Glass / Diffusor Tempered safety glass Impact protection IK10 Ingress protection IP67 Input voltage 220-240V 50/60Hz **Insulation class** Class I 4.06 kg Weight **LED** module Multi-chip high power LEDs on metal-core PCB Internal LED driver Driver **Driver surge** 1/1 kV protection **Power factor** > 0.90

Operating temperature

Through wiring

Power cord 12" of rubber-sheated power cord

Single power cord entry

-30...50°C

Accessories (To be ordered separately)

Mounting accessories Mounting accessories Mounting accessories







Case removing vacuum

Connector set - 5pole

Junction Box

160404012

141407400

141901135

Mounting accessories



Plastic case for **ZEROX M**

007502092

Project name					Туре	Quantity	
Date			Note				

LR9017.690-EN-S-700-830-__-SS-__

Light distribution	Rated input power	Color temperature	Control	Product colors
[S] Spot - NEMA Type 0 - 7°	[700] 18 W	[830] 3000 K CRI 80	[ONOFF] On/Off	[SS] Stainless steel
[N]	[350] 10 W	[827] 2700 K CRI 80	[DALI] DALI	
Narrow - NEMA Type 2 - 26°	[500] 13 W	[740] 4000 K CRI 70		
		[840] 4000 K CRI 80		
Extras	Accessories (To be ordered separately)			
Consult the factory	Mounting			
[UNI] 120-277V 50/60Hz	accessories [160404012] Case removing vacuum			
	[141407400] Connector set - 5-pole			
	[141901135] Junction Box			
	[007502092] Plastic case for ZEROX M			