## **DOMINI AFX MIDI 1 Module** Duo











#### LB6047.872-EN-T2-2-350-840-ONOFF-EN-C1









[T2] Type II, Asymmetric, Side throw

#### **Variant**

**Light distribution** [T2] 134x52° **Delivered lumens flux** 1983 lm 20 W Rated input power **Colour temperature** 4000 K CRI 80 **Luminaire efficacy** 110 lm/W 16 LED Lamp **MacAdam Ellipse** 4 SDCM **BUG** rating B0-U0-G0 Lifetime L90B50 (hour) >102,000 Lifetime L80B50 (hour) >102,000

### Options

#### Technical information

recinited inform	duon
Mounting	Surface mountable
Housing	Corrosion resistant, extruded, marine grade
	aluminum housing
Finishing	Chromate conversion pretreatment followed by
	electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Liquid silicone
Lens / Reflector	PMMA lens with high optical efficiency
Glass / Diffusor	Tempered safety glass
Impact protection	IK08
Ingress protection	IP66
Input voltage	220-240V 50/60Hz
Insulation class	Class I
Weight	7.43 kg
LED module	High power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge	6/6 kV
protection	
Power factor	> 0.95
Through wiring	Single cable entry
Operating	-4050°C
temperature	
Cable	0.5 m of flexible cable
Notes	3000K CCT or warmer must be selected to be

Başkent OSB 22. Cd. No: 2, Malıköy, Temelli, Sincan, 06909 Ankara, Turkey +90 312 267 54 30 info@hepergroup.com

### HEPER Europe GmbH

Ahornweg 5a, 58675 Hemer, Germany +49 237 2901 2975 infoEU@hepergroup.com We reserve the right to change specifications without prior written notice. Edition: 19.05.2024. For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

DarkSky International certified.

### Accessories (To be ordered separately)

Anchorages

Flange covers





**90AJ001** 90AJ001

**C6A2A** C6A2A

Project na	me			Туре	Quantity		
Date			Note				

# LB6047.872-EN-T2-2-350-840-ONOFF-EN-C1-\_\_-\_--\_--

Light distribution	Rated input power	Colour temperature	Control	Product colours
[T2] Type II, Asymmetric,	[ <b>350</b> ] 20 W	[840] 4000 K CRI 80	[ONOFF] On/Off	[HM1] Black
IT1] Type I, Asymmetric, Side throw - 110x45°  IT3] Type III, Asymmetric, Side throw - 131x60°  IT4] Type IV, Asymmetric, Forward throw - 114x65°  IT5] Type V, Symmetric - 115°	[500] 27 W [700] 37 W	[827] 2700 K CRI 80 [830] 3000 K CRI 80 [740] 4000 K CRI 70		[HM2] Dark grey  [HM3] Anthracite grey  [HM4] Light grey  [HM5] White  [HM6] Bronze  [CC] Custom colour (Pleas specify RAL code)
Height	Extras	Accessories (To be ordered separately)		I
[H1] 1m [HC]	Light output	Anchorages	-	
	[BS] Backlight Shield	[ <b>90AJ001</b> ] 90AJ001		
	Consult the factory	Flange covers	-	
	[UNI] 120-277V 50/60Hz	[ <b>C6A2A</b> ] C6A2A		
	Luminaire body options			
	[DPC] Double powder coating			