



# PRIFMA AFX 1 Module Duo



LL2044.861-EN-T5-700-830



[T5]  
Type V

## Configuration

|                       |               |
|-----------------------|---------------|
| Light distribution    | [T5] 117°     |
| Delivered lumens flux | 7645 lm       |
| Rated input power     | 70 W          |
| Color temperature     | 3000 K CRI 80 |
| Luminaire efficacy    | 114 lm/W      |
| Lamp                  | 32 LED        |
| Color Deviation       | 3 SDCM        |
| BUG rating            | B2-U0-G0      |
| Lifetime L90 (hour)   | >102,000      |
| Lifetime L80 (hour)   | >102,000      |

## Options

## Technical information

|                         |                                                                                                                       |
|-------------------------|-----------------------------------------------------------------------------------------------------------------------|
| Mounting                | Surface mountable                                                                                                     |
| Housing                 | Corrosion resistant, marine grade aluminum housing                                                                    |
| Finishing               | Chromate conversion pretreatment followed by electrostatic powder coating                                             |
| Fasteners               | Stainless steel (AISI 304 / EN 1.4301 grade)                                                                          |
| Gasket                  | Liquid silicone                                                                                                       |
| Lens / Reflector        | PMMA lens with high optical efficiency                                                                                |
| Glass / Diffusor        | Tempered safety glass                                                                                                 |
| Impact protection       | IK08                                                                                                                  |
| Ingress protection      | IP66                                                                                                                  |
| Input voltage           | 220-240V 50/60Hz                                                                                                      |
| Insulation class        | Class I                                                                                                               |
| Weight                  | 25.58 kg (3 m), 31.07 kg (4 m), 36.56 kg (5 m), 104.02 kg (6 m)                                                       |
| LED module              | High power LEDs on metal-core PCB                                                                                     |
| Driver                  | Internal LED driver                                                                                                   |
| Driver surge protection | 6/4 kV                                                                                                                |
| Power factor            | > 0.96                                                                                                                |
| Through wiring          | Single power cord entry                                                                                               |
| Operating temperature   | -40...50°C                                                                                                            |
| Power cord              | 20" of outdoor use rated flexible power cord                                                                          |
| Pole detail             | Poles are supplied with flange plate. Flange cover and anchorage can be ordered separately. Embedded base is optional |
| Notes                   | 3000K CCT or warmer must be selected to be DarkSky International certified.                                           |

# Poles (Included)

---

## Product specific poles with base plate



| Configuration code | Height | Diameter /<br>Dimensions | Spigot / End<br>diameter |
|--------------------|--------|--------------------------|--------------------------|
| PAFD.R03.T001-H3   | 10'    | 7.1x2.8"                 |                          |
| PAFD.R03.T001-H4   | 13.1'  | 7.1x2.8"                 |                          |

|              |  |  |      |  |      |  |          |  |
|--------------|--|--|------|--|------|--|----------|--|
| Project name |  |  |      |  | Type |  | Quantity |  |
| Date         |  |  | Note |  |      |  |          |  |

LL2044.861-EN-T5-700-830- - - - -

| Light distribution                                                                                                                                                                                                                                                   | Rated input power                                | Color temperature             | Control                  | Product colors                                           |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------|-------------------------------|--------------------------|----------------------------------------------------------|
| <b>[T5]</b><br>Type V - 117°                                                                                                                                                                                                                                         | <b>[700]</b><br>70 W                             | <b>[830]</b><br>3000 K CRI 80 | <b>[ONOFF]</b><br>On/Off | <b>[HM1]</b><br>Black                                    |
| <b>[P4]</b><br>Pedestrian crosswalk<br>distribution - 20x78°<br><br><b>[T1]</b><br>Type I - 111x48°<br><br><b>[T2]</b><br>Type II - 133x48°<br><br><b>[T2]</b><br>Type II - 149x54°<br><br><b>[T3]</b><br>Type III - 143x63°<br><br><b>[T4]</b><br>Type IV - 117x64° | <b>[350]</b><br>36 W<br><br><b>[500]</b><br>50 W | <b>[827]</b><br>2700 K CRI 80 | <b>[DALI]</b><br>DALI    | <b>[HM2]</b><br>Dark gray                                |
|                                                                                                                                                                                                                                                                      |                                                  | <b>[740]</b><br>4000 K CRI 70 |                          | <b>[HM3]</b><br>Anthracite gray                          |
|                                                                                                                                                                                                                                                                      |                                                  | <b>[840]</b><br>4000 K CRI 80 |                          | <b>[HM4]</b><br>Light gray                               |
|                                                                                                                                                                                                                                                                      |                                                  |                               |                          | <b>[HM5]</b><br>White                                    |
|                                                                                                                                                                                                                                                                      |                                                  |                               |                          | <b>[HM6]</b><br>Bronze                                   |
|                                                                                                                                                                                                                                                                      |                                                  |                               |                          | <b>[CC]</b><br>Custom color (Please<br>specify RAL code) |
|                                                                                                                                                                                                                                                                      | <b>[WD]</b><br>Wooden                            |                               |                          |                                                          |
| <b>Height</b>                                                                                                                                                                                                                                                        | <b>Extras</b>                                    |                               |                          |                                                          |
| <b>[H3]</b><br>10'<br><br><b>[H4]</b><br>13.1'<br><br><b>[H5]</b><br>16.4'<br><br><b>[H6]</b><br>19.7'<br><br><b>[HC]</b>                                                                                                                                            | <b>Light output</b>                              |                               |                          |                                                          |
|                                                                                                                                                                                                                                                                      | <b>[BS]</b><br>Backlight Shield                  |                               |                          |                                                          |
|                                                                                                                                                                                                                                                                      | <b>[CLO]</b><br>Constant light output            |                               |                          |                                                          |
|                                                                                                                                                                                                                                                                      | <b>Consult the factory</b>                       |                               |                          |                                                          |
|                                                                                                                                                                                                                                                                      | <b>[UNI]</b><br>120-277V 50/60Hz                 |                               |                          |                                                          |
|                                                                                                                                                                                                                                                                      | <b>Luminaire body<br/>options</b>                |                               |                          |                                                          |
|                                                                                                                                                                                                                                                                      | <b>[DPC]</b><br>Double powder<br>coating         |                               |                          |                                                          |