
### **URBAN BOLLARD Ch**

### LB6061.547-US-SYM-350-830-ONOFF



# Ø200 mm 7 7/8' 1006 mm 39 39/64" (6)





Symmetric

### Configuration

**Light distribution** [SYM] 114° Delivered lumens flux 2124 lm Rated input power 30 W **Color temperature** 3000 K CRI 80 Luminaire efficacy 70 lm/W Lamp **12 LED Color Deviation** 3 SDCM B2-U0-G1 **BUG** rating Lifetime L90 (hour) >60,000 Lifetime L80 (hour) >60,000

### Options

Technical information Mounting Surface mountable Housing Corrosion resistant, extruded, marine grade aluminum housing Finishing Chromate conversion pretreatment followed by electrostatic powder coating **Fasteners** Stainless steel (AISI 304 / EN 1.4301 grade) Gasket Silicone Lens / Reflector High reflectance aluminium coating, multifaceted micro reflector Glass / Diffusor UV stable, bio-based polycarbonate diffusor Impact protection **IK08** Ingress protection IP65 Input voltage 120-277V 50/60Hz **Insulation class** Class I Weight 26 lbs **LED** module Multi-chip high power LEDs on metal-core PCB Driver Internal LED driver **Driver surge** 2/2 kV protection **Power factor** > 0.90 Through wiring Single power cord entry Operating -40...50°C temperature 20" of outdoor use rated flexible power cord Power cord Notes

As standard, 2 sockets of mono-phase are provided. Upon request, a maximum of 3 sockets with different socket types can be also provided.

# Accessories (To be ordered separately)

### Anchor bolts



### 630J014

630J014

Project name					Quantity	
Date		Note				

## LB6061.547-US-SYM-350-830-ONOFF-\_\_--\_

Light distribution	Rated input power	Color temperature	Control	Product colors
<b>[SYM]</b> Symmetric - 114°	[ <b>350</b> ] 30 W	[ <b>830]</b> 3000 K CRI 80	[ONOFF] On/Off	[HM1] Black
		[ <b>827</b> ] 2700 K CRI 80		[HM2] Dark gray
		[740] 4000 K CRI 70 [840] 4000 K CRI 80		[HM3] Anthracite gray
				[HM4] Light gray
				[HM5] White
				[HM6] Bronze
				Custom color (Please specify RAL code)
Height	Extras	Accessories (To be ordered separately)		
[H1]	Luminaire body	Anchor bolts		
3.3' [HC]	options  [DPC]  Double powder coating	[ <b>630J014</b> ] 630J014		