


# DOMINO AFX 2 Module Duo



LP4091.862-US-T2-500-740



[T2]  
Type II

## Configuration

|                       |               |
|-----------------------|---------------|
| Light distribution    | [T2] 133x48°  |
| Delivered lumens flux | 13395 lm      |
| Rated input power     | 97 W          |
| Color temperature     | 4000 K CRI 70 |
| Luminaire efficacy    | 134 lm/W      |
| Lamp                  | 64 LED        |
| Color Deviation       | 4 SDCM        |
| BUG rating            | B1-U0-G1      |
| Lifetime L90 (hour)   | >102,000      |
| Lifetime L80 (hour)   | >102,000      |

## Options

## Technical information

|                         |                                                                                                                       |
|-------------------------|-----------------------------------------------------------------------------------------------------------------------|
| Mounting                | Surface mountable                                                                                                     |
| Housing                 | Corrosion resistant, marine grade aluminum housing                                                                    |
| Finishing               | Chromate conversion pretreatment followed by electrostatic powder coating                                             |
| Fasteners               | Stainless steel (AISI 304 / EN 1.4301 grade)                                                                          |
| Gasket                  | Liquid silicone                                                                                                       |
| Lens / Reflector        | PMMA lens with high optical efficiency                                                                                |
| Glass / Diffusor        | Tempered safety glass                                                                                                 |
| Impact protection       | IK08                                                                                                                  |
| Ingress protection      | IP66                                                                                                                  |
| Input voltage           | 120-277V 50/60Hz                                                                                                      |
| Insulation class        | Class I                                                                                                               |
| Weight                  | 118.69 lbs (13'), 129.91 lbs (16.5'), 141.13 lbs (20')                                                                |
| LED module              | High power LEDs on metal-core PCB                                                                                     |
| Driver                  | Internal LED driver                                                                                                   |
| Driver surge protection | 10/6 kV                                                                                                               |
| Power factor            | > 0.95                                                                                                                |
| Through wiring          | Single power cord entry                                                                                               |
| Operating temperature   | -40...50°C                                                                                                            |
| Power cord              | 20" of outdoor use rated flexible power cord                                                                          |
| Pole detail             | Poles are supplied with flange plate. Flange cover and anchorage can be ordered separately. Embedded base is optional |
| Notes                   | 3000K CCT or warmer must be selected to be DarkSky International certified.                                           |

# Poles (Included)

---

## Product specific poles with base plate



| Configuration code | Height | Diameter /<br>Dimensions | Spigot / End<br>diameter |
|--------------------|--------|--------------------------|--------------------------|
| PAFD.R01.T003-H4   | 13.1'  | 7.1x4.7"                 |                          |
| PAFD.R01.T003-H5   | 16.4'  | 7.1x4.7"                 |                          |
| PAFD.R01.T003-H6   | 19.7'  | 7.1x4.7"                 |                          |

|              |  |  |      |  |      |  |          |  |
|--------------|--|--|------|--|------|--|----------|--|
| Project name |  |  |      |  | Type |  | Quantity |  |
| Date         |  |  | Note |  |      |  |          |  |

**LP4091.862-US-T2-500-740-**\_\_\_\_\_-\_\_\_\_\_-\_\_\_\_\_-\_\_\_\_\_-\_\_\_\_\_

| Light distribution                                           | Rated input power     | Color temperature             | Control                  | Product colors                                           |
|--------------------------------------------------------------|-----------------------|-------------------------------|--------------------------|----------------------------------------------------------|
| <b>[T2]</b><br>Type II - 133x48°                             | <b>[500]</b><br>97 W  | <b>[740]</b><br>4000 K CRI 70 | <b>[ONOFF]</b><br>On/Off | <b>[HM1]</b><br>Black                                    |
| <b>[P4]</b><br>Pedestrian crosswalk<br>distribution - 20x78° | <b>[350]</b><br>68 W  | <b>[827]</b><br>2700 K CRI 80 | <b>[0-10V]</b><br>0-10V  | <b>[HM2]</b><br>Dark gray                                |
| <b>[T1]</b><br>Type I - 111x48°                              | <b>[700]</b><br>135 W | <b>[830]</b><br>3000 K CRI 80 |                          | <b>[HM3]</b><br>Anthracite gray                          |
| <b>[T3]</b><br>Type III - 143x63°                            |                       | <b>[840]</b><br>4000 K CRI 80 |                          | <b>[HM4]</b><br>Light gray                               |
| <b>[T4]</b><br>Type IV - 117x64°                             |                       |                               |                          | <b>[HM5]</b><br>White                                    |
| <b>[T5]</b><br>Type V - 117°                                 |                       |                               |                          | <b>[HM6]</b><br>Bronze                                   |
|                                                              |                       |                               |                          | <b>[CC]</b><br>Custom color (Please<br>specify RAL code) |

| Height        | Extras                         |
|---------------|--------------------------------|
| [H4]<br>13.1' | <b>Connectivity</b>            |
| [H5]<br>16.4' | [NM7]<br>7 Pin NEMA socket     |
| [H6]<br>19.7' | <b>Consult the factory</b>     |
| [HC]          | [MS]<br>Motion sensor          |
|               | <b>Luminaire body options</b>  |
|               | [DPC]<br>Double powder coating |