

HANDRA Side - Ø48 mm



IK10 IP65





LH5005.595-US-SLSH-350-830-CC-3V-350-C3



22 mm
55/64"



40 mm
1 37/64"



[SLSH]

Special linear, Side
throw

Variant

Light distribution	[SLSH] 42x54°
Delivered lumens flux	40 lm
Rated input power	1 W
Colour temperature	3000 K CRI 80
Luminaire efficacy	40 lm/W
Lamp	1 LED
MacAdam Ellipse	3 SDCM
Lifetime L90B50 (hour)	>102,000
Lifetime L80B50 (hour)	>102,000

Options

Technical information




Housing	Corrosion resistant, die-cast, marine grade aluminum housing
Finishing	Chromate conversion pretreatment followed by electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Liquid gasket
Lens / Reflector	High reflectance aluminium coating
Glass / Diffusor	Custom Design PMMA Diffusor
Impact protection	IK10
Ingress protection	IP65
Input voltage	3 Vdc (Max) 350 mA
Insulation class	Class III
Weight	0.1 lbs
LED module	High power LEDs on metal-core PCB
Driver	External LED driver
Through wiring	Single cable entry
Operating temperature	-25...50°C
Cable	0.2 m of flexible cable
Packing box dimensions	2 3/4" * 2 3/4" * 2 3/4"

HPR Pazarlama A.Ş.
Başkent OSB 22. Cd. No: 2, Malıköy, Temelli,
Sincan, 06909 Ankara, Turkey
+90 312 267 54 30
info@hepergroup.com

HEPER Europe GmbH
Ahornweg 5a, 58675
Hemer, Germany
+49 237 2901 2975
infoEU@hepergroup.com

We reserve the right to change specifications without prior written notice. Edition: 05.05.2024.
For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

Accessories (To be ordered separately)

Mounting accessories	Mounting accessories	Mounting accessories
		
0-10V Driver within an IP67 box for 1 to 6 HANDRA modules	0-10V Driver within an IP67 box for 7 to 15 HANDRA modules	0-10V Driver within an IP67 box for 16 to 35 HANDRA modules
007502066	007502067	007502068

Project name		Type		Quantity	
Date		Note			
LH5005.595-US-SLSH-350-830-__-CC-3V-350-C3-__					

Light distribution	Rated input power	Colour temperature	Control	Product colours
[SLSH] Special linear, Side throw - 42x54°	[350] 1 W	[830] 3000 K CRI 80		[HM1] Black
		[827] 2700 K CRI 80		[HM2] Dark grey
		[740] 4000 K CRI 70		[HM3] Anthracite grey
		[840] 4000 K CRI 80		[HM4] Light grey
				[HM5] White
				[HM6] Bronze
				[CC] Custom colour (Please specify RAL code)
Accessories (<i>To be ordered separately</i>)				
Mounting accessories				
[007502066] 0-10V Driver within an IP67 box for 1 to 6 HANDRA modules				
[007502067] 0-10V Driver within an IP67 box for 7 to 15 HANDRA modules				
[007502068] 0-10V Driver within an IP67 box for 16 to 35 HANDRA modules				