

VERTEX 1 Module

LB6064.591-EN-SLFB-350-740-EN-C1









[SLFB] Special linear, Forward throw

HPR Pazarlama A.Ş.

+90 312 267 54 30

info@hepergroup.com

Sincan, 06909 Ankara, Turkey

Başkent OSB 22. Cd. No: 2, Malıköy, Temelli,

HEPER Europe GmbH

Ahornweg 5a, 58675 Hemer, Germany +49 237 2901 2975 infoEU@hepergroup.com We reserve the right to change specifications without prior written notice. Edition: 21.05.2024. For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.





Variant

Light distribution	[SLFB] 144x41°
Delivered lumens flux	473 lm
Rated input power	8 W
Colour temperature	4000 K CRI 70
Luminaire efficacy	59 lm/W
Lamp	6 LED
MacAdam Ellipse	3 SDCM
BUG rating	B2-U0-G1
Lifetime L90B50 (hour)	>60,000
Lifetime L80B50 (hour)	>60,000

Options

Technical information

Mounting	Surface mountable
Housing	Corrosion resistant, extruded, marine grade
	aluminum housing
Finishing	Chromate conversion pretreatment followed by
	electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Liquid silicone
Lens / Reflector	High reflectance aluminium coating,
	multifaceted micro reflector
Glass / Diffusor	Tempered safety glass
Impact protection	IK08
Ingress protection	IP66
Input voltage	220-240V 50/60Hz
Insulation class	Class I
Weight	4.51 kg
LED module	Multi-chip high power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge	1/1 kV
protection	
Power factor	> 0.90
Through wiring	Single cable entry
Operating	-2550°C
temperature	
Cable	0.5 m of flexible cable



Accessories (To be ordered separately)





6281005

6281005

HPR Pazarlama A.Ş. Başkent OSB 22. Cd. No: 2, Malıköy, Temelli, Sincan, 06909 Ankara, Turkey +90 312 267 54 30 info@hepergroup.com HEPER Europe GmbH

Ahornweg 5a, 58675 Hemer, Germany +49 237 2901 2975 infoEU@hepergroup.com We reserve the right to change specifications without prior written notice. Edition: 21.05.2024. For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

2/3

Project na	me				Туре	Quantity	
Date	ite		Note				
LB6064.	591-EN-S	LFB-350-7	740EI	N-C1			

Light distribution	Rated input power	Colour temperature	Control	Product colours
[SLFB] Special linear,	[350] 8 W	[740] 4000 K CRI 70	[ONOFF] On/Off	[HM1] Black
Forward throw - 144x41°		[827] 2700 K CRI 80	[DALI] DALI	[HM2] Dark grey
		[830] 3000 K CRI 80		[HM3] Anthracite grey
		[840] 4000 K CRI 80		[HM4] Light grey
				[HM5] White
				[HM6] Bronze
				[CC] (Clustom colour (Pleas specify RAL code)
				[WD] Wooden
Height	Extras	Accessories (To be ordered separately)		
[H0.50]	Luminaire body	Anchorages		
50cm [HC]	options [DPC] Double powder coating	[6281005] 6281005		

HEPER Europe GmbH

Ahornweg 5a, 58675 Hemer, Germany +49 237 2901 2975 infoEU@hepergroup.com We reserve the right to change specifications without prior written notice. Edition: 21.05.2024. For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.