


# WINGS ML EVO 2 Module



LL2012.682-US-T2-700-740-ONOFF



[T2]  
Type II

## Configuration

Light distribution	[T2] 130x85°
Delivered lumens flux	6897 lm
Rated input power	70 W
Color temperature	4000 K CRI 70
Luminaire efficacy	98 lm/W
Lamp	8 LED
Color Deviation	5 SDCM
BUG rating	B2-U0-G1
Photobiological safety	Risk group 0
Lifetime L90 (hour)	>60,000
Lifetime L80 (hour)	>60,000

## Options

## Technical information

Mounting	Surface mountable
Housing	Corrosion resistant, marine grade aluminum housing
Finishing	Chromate conversion pretreatment followed by electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Liquid silicone
Lens / Reflector	High reflectance aluminium coating, multifaceted micro reflector
Glass / Diffusor	Bio-based, enriched with bisphenol A diffusor
Impact protection	IK08
Ingress protection	IP66
Input voltage	120-277V 50/60Hz
Insulation class	Class I
Weight	110.88 lbs (10'), 127 lbs (13')
LED module	Multi-chip high power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge protection	6/6 kV
Power factor	> 0.95
Through wiring	Single power cord entry
Operating temperature	-40...50°C
Pole detail	Poles are supplied with flange plate. Flange cover and anchorage can be ordered separately. Embedded base is optional








# Poles (Included)

## Product specific poles with base plate



Configuration code	Height	Diameter / Dimensions	Spigot / End diameter
PAFD.R01.T002-H3	10'	7.3x4.7"	
PAFD.R01.T002-H4	13.1'	7.3x4.7"	

Project name					Type		Quantity	
Date			Note					
LL2012.682-US-T2-700-740-ONOFF-__-__-__								

Light distribution	Rated input power	Color temperature	Control	Product colors	
<b>[T2]</b> Type II - 130x85°	<b>[700]</b> 70 W	<b>[740]</b> 4000 K CRI 70	<b>[ONOFF]</b> On/Off	<b>[HM1]</b> Black	
		<b>[827]</b> 2700 K CRI 80		<b>[HM2]</b> Dark gray	
		<b>[830]</b> 3000 K CRI 80		<b>[HM3]</b> Anthracite gray	
		<b>[840]</b> 4000 K CRI 80		<b>[HM4]</b> Light gray	
		<b>[HM5]</b> White			
		<b>[HM6]</b> Bronze			
				<b>[CC]</b> Custom color (Please specify RAL code)	
<b>Height</b>	<b>Extras</b>				
<b>[H3]</b> 10'	<b>Luminaire body options</b>				
<b>[H4]</b> 13.1'	<b>[DPC]</b> Double powder coating				
<b>[HC]</b>					