ZEROX Hybrid











Ground recessed mountable

LR9005.695-EN-N-350-830-EN-C1-SS











Narrow

Variant

Light distribution [N] 26° Delivered lumens flux 1947 lm Rated input power 18 W **Colour temperature** 3000 K CRI 80 **Luminaire efficacy** 97 lm/W Lamp 4 LED MacAdam Ellipse 5 SDCM >72,600 Lifetime L90B50 (hour) Lifetime L80B50 (hour) >72,600

Options

Technical information

Mounting Housing Corrosion resistant stainless steel housing (AISI 316L / EN 1.4571 grade) Stainless steel (AISI 304 / EN 1.4301 grade) **Fasteners** Gasket Silicone Lens / Reflector High reflectance aluminium coating Glass / Diffusor Tempered safety glass Impact protection IK10 Ingress protection IP67 Input voltage 220-240V 50/60Hz

Insulation class Class I 6.85 kg Weight Multi-chip high power LEDs on metal-core PCB **LED** module Internal LED driver Driver **Driver surge** 10/6 kV

protection

Power factor > 0.95 Through wiring Single cable entry -40...50°C Operating

temperature

Cable 0.3 m of rubber-sheated cable Notes QUICK SHIP: Some variants will be delivered faster. Please consult the factory.

Accessories (To be ordered separately)

Mounting accessories Mounting accessories Mounting accessories









Case removing vacuum

Connector set - 5pole

Junction Box

160404012 141407400 141901135

Mounting accessories



Plastic case for **ZEROX**

007501028

Project name					Туре	Quantity	
Date	ate		Note				

LR9005.695-EN-N-350-830-___-EN-C1-SS-__

Light distribution	Rated input power	Colour temperature	Control	Product colours	
[N] Narrow - 26°	[350] 18 W	[830] 3000 K CRI 80	[ONOFF] On/Off	[SS] Stainless steel	
[S] Spot - 7°	[500] 28 W	[827] 2700 K CRI 80 [740] 4000 K CRI 70 [840] 4000 K CRI 80	[DALI] DALI		
Extras	Accessories (To be ordered separately)				
Consult the factory	Mounting accessories				
[UNI] 120-277V 50/60Hz	[160404012] Case removing vacuum [141407400] Connector set - 5-pole [141901135] Junction Box [007501028] Plastic case for ZEROX				