



# ZEROX Hybrid



LR9005.695-EN-N-500-830-SS



[N]

Narrow - NEMA Type 2

## Configuration

Light distribution	[N] 26°
Delivered lumens flux	2622 lm
Rated input power	28 W
Color temperature	3000 K CRI 80
Luminaire efficacy	93 lm/W
Lamp	4 LED
Color Deviation	5 SDCM
Lifetime L90 (hour)	>72,600
Lifetime L80 (hour)	>72,600

## Options

## Technical information


Mounting	Ground recessed mountable
Housing	Corrosion resistant stainless steel housing (AISI 316L / EN 1.4571 grade)
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone
Lens / Reflector	High reflectance aluminium coating
Glass / Diffuser	Tempered safety glass
Impact protection	IK10
Ingress protection	IP67
Input voltage	220-240V 50/60Hz
Insulation class	Class I
Weight	6.85 kg
LED module	Multi-chip high power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge protection	10/6 kV
Power factor	> 0.95
Through wiring	Single power cord entry
Operating temperature	-40...50°C
Power cord	12" of rubber-sheathed power cord
Notes	QUICK SHIP: Some variants will be delivered faster. Please consult the factory.

Accessories (To be ordered separately)


Mounting accessories    Mounting accessories    Mounting accessories



**Case removing  
vacuum**  
160404012



**Connector set - 5-  
pole**  
141407400



**Junction Box**  
141901135


Mounting accessories



**Plastic case for  
ZEROX**  
007501028

Project name				Type		Quantity	
Date		Note					

**LR9005.695-EN-N-500-830-\_\_-SS-\_\_**

Light distribution	Rated input power	Color temperature	Control	Product colors
<b>[N]</b> Narrow - NEMA Type 2 - 26°	<b>[500]</b> 28 W	<b>[830]</b> 3000 K CRI 80	<b>[ONOFF]</b> On/Off	<b>[SS]</b>  Stainless steel
<b>[S]</b> Spot - NEMA Type 0 - 7°	<b>[350]</b> 18 W	<b>[827]</b> 2700 K CRI 80  <b>[740]</b> 4000 K CRI 70  <b>[840]</b> 4000 K CRI 80	<b>[DALI]</b> DALI	
Extras	Accessories ( <i>To be ordered separately</i> )			
Consult the factory	Mounting accessories			
<b>[UNI]</b> 120-277V 50/60Hz	<b>[160404012]</b> Case removing vacuum  <b>[141407400]</b> Connector set - 5-pole  <b>[141901135]</b> Junction Box  <b>[007501028]</b> Plastic case for ZEROX			