
ZEROX S Hybrid

CE 🕵 🖳 IK10 IP67



LR9016.693-EN-N-350-830-EN-C1-SS





Narrow

Variant

Light distribution	[N] 26°
Delivered lumens flux	485 lm
Rated input power	5 W
Colour temperature	3000 K CRI 80
Luminaire efficacy	97 lm/W
Lamp	1 LED
MacAdam Ellipse	5 SDCM
Lifetime L90B50 (hour)	>72,600
Lifetime L80B50 (hour)	>72,600

Options

Technical information

Mounting	Ground recessed mountable
Housing	Corrosion resistant stainless steel housing (AISI
0	316L / EN 1.4571 grade)
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone
Lens / Reflector	High reflectance aluminium coating
Glass / Diffusor	Tempered safety glass
Impact protection	IK10
Ingress protection	IP67
Input voltage	220-240V 50/60Hz
Insulation class	Class I
Weight	2.81 kg
LED module	Multi-chip high power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge	1/1 kV
protection	
Power factor	> 0.91
Through wiring	Single cable entry
Operating	-2550°C
temperature	-2350 C
Cable	0.3 m of rubber-sheated cable
Cable	0.5 III OI TUDDEI-SITEALEU CADIE


HPR Pazarlama A.Ş.

Başkent OSB 22. Cd. No: 2, Malıköy, Temelli, Sincan, 06909 Ankara, Turkey +90 312 267 54 30 info@hepergroup.com

HEPER Europe GmbH

Ahornweg 5a, 58675 Hemer, Germany +49 237 2901 2975 infoEU@hepergroup.com We reserve the right to change specifications without prior written notice. Edition: 18.05.2024. For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

Accessories (To be ordered separately)





Plastic case for ZEROX S

007502091

HPR Pazarlama A.Ş. Başkent OSB 22. Cd. No: 2, Malıköy, Temelli, Sincan, 06909 Ankara, Turkey +90 312 267 54 30 info@hepergroup.com HEPER Europe GmbH

Ahornweg 5a, 58675 Hemer, Germany +49 237 2901 2975 infoEU@hepergroup.com We reserve the right to change specifications without prior written notice. Edition: 18.05.2024. For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

2/3

Project na	roject name		Туре	Quantity		
Date		Note				
LR9016.693-EN-N-350-830EN-C1-SS						

Light distribution	Rated input power	Colour temperature	Control	Product colours
[N] Narrow - 26°	[350] 5 W	[830] 3000 K CRI 80	[ONOFF] On/Off	[SS] Stainless steel
[S] Spot - 7°	[700] 10 W	[827] 2700 K CRI 80	[DALI] DALI	
	[500] 6 W	[740] 4000 K CRI 70		
		[840] 4000 K CRI 80		
Extras	Accessories (To be ordered separately)			
Consult the factory	Mounting			
[UNI] 120-277V 50/60Hz	accessories	-		
	[160404012] Case removing vacuum			
	[141407400] Connector set - 5-pole			
	[141901135] Junction Box			
	[007502091] Plastic case for ZEROX S			

HEPER Europe GmbH

Ahornweg 5a, 58675 Hemer, Germany +49 237 2901 2975 infoEU@hepergroup.com We reserve the right to change specifications without prior written notice. Edition: 18.05.2024. For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.