ZEROX M Hybrid











LR9017.690-EN-N-500-830-EN-C1-SS











Narrow

Variant

Light distribution [N] 26° **Delivered lumens flux** 1309 lm Rated input power 13 W **Colour temperature** 3000 K CRI 80 100 lm/W **Luminaire efficacy** Lamp 2 LED MacAdam Ellipse 5 SDCM Lifetime L90B50 (hour) >72,600 Lifetime L80B50 (hour) >72,600

Options

Technical information

Mounting	Ground recessed mountable
Housing	Corrosion resistant stainless steel housing (AISI
	316L / EN 1.4571 grade)
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone
Lens / Reflector	High reflectance aluminium coating
Glass / Diffusor	Tempered safety glass
Impact protection	IK10
Ingress protection	IP67
Input voltage	220-240V 50/60Hz
Insulation class	Class I
Weight	4.06 kg
LED module	Multi-chip high power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge	1/1 kV
protection	
Power factor	> 0.90
Through wiring	Single cable entry

Operating temperature

Cable 0.3 m of rubber-sheated cable

Başkent OSB 22. Cd. No: 2, Malıköy, Temelli, Sincan, 06909 Ankara, Turkey +90 312 267 54 30 info@hepergroup.com

HEPER Europe GmbH

Ahornweg 5a, 58675 Hemer, Germany +49 237 2901 2975 infoEU@hepergroup.com We reserve the right to change specifications without prior written notice. Edition: 19.05.2024. For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

-30...50°C

Accessories (To be ordered separately)

Mounting accessories Mounting accessories Mounting accessories









Case removing vacuum

Connector set - 5pole

Junction Box

160404012

141407400

141901135

Mounting accessories



Plastic case for **ZEROX M**

007502092

Project na	Project name		Туре	Quantity		
Date			Note			

LR9017.690-EN-N-500-830-___-EN-C1-SS-__

Light distribution	Rated input power	Colour temperature	Control	Product colours
[N] Narrow - 26°	[500] 13 W	[830] 3000 K CRI 80	[ONOFF] On/Off	[SS] Stainless steel
[S] Spot - 7°	[700] 18 W	[827] 2700 K CRI 80	[DALI] DALI	
	[350] 10 W	[740] 4000 K CRI 70		
		[840] 4000 K CRI 80		
Extras	Accessories (To be ordered separately)			
Consult the factory	Mounting			
[UNI] 120-277V 50/60Hz	accessories	-		
	[160404012] Case removing vacuum			
	[141407400] Connector set - 5-pole			
	[141901135] Junction Box			
	[007502092] Plastic case for ZEROX M			
	I			