
ZEROX M Hybrid


heper '

LR9017.690-US-S-350-840-SS











[S] Spot - NEMA Type 0

Configuration

Light distribution [S] 7° Delivered lumens flux 1077 lm Rated input power 10 W **Color temperature** 4000 K CRI 80 107 lm/W **Luminaire efficacy** Lamp 2 LED **Color Deviation** 5 SDCM Lifetime L90 (hour) >72,600 Lifetime L80 (hour) >72,600

Options

Technical information

Mounting Ground recessed mountable Housing Corrosion resistant stainless steel housing (AISI 316L / EN 1.4571 grade) **Fasteners** Stainless steel (AISI 304 / EN 1.4301 grade) Gasket Silicone Lens / Reflector High reflectance aluminium coating Glass / Diffusor Tempered safety glass Impact protection IK10 Ingress protection IP67 Input voltage 120-277V 50/60Hz **Insulation class** Class I 8.9 lbs Weight Multi-chip high power LEDs on metal-core PCB **LED** module Internal LED driver Driver **Driver surge** 2/2 kV protection **Power factor** > 0.90

Operating temperature

Through wiring

Power cord 12" of rubber-sheated power cord

Single power cord entry

-30...50°C

Mounting accessories



Connector set - 5pole

141407400



Case removing vacuum

160404012

Mounting accessories Mounting accessories



Plastic case for **ZEROX M**

007502092

Project na	me		Туре	Quantity	
Date		Note			

LR9017.690-US-S-350-840-___-SS

Light distribution	Rated input power	Color temperature	Control	Product colors	
[S] Spot - NEMA Type 0 -	[350] 10 W	[840] 4000 K CRI 80	[ONOFF] On/Off	[SS] Stainless steel	
7° [N]	[700] 18 W	[827] 2700 K CRI 80	[0-10V] 0-10V		
Narrow - NEMA Type 2 - 26°	[500] 13 W	[830] 3000 K CRI 80			
		[740] 4000 K CRI 70			
Accessories (Included)	Accessories (To be ordered separately)				
Mounting accessories	Mounting accessories				
[141407400] Connector set - 5-pole	[160404012] Case removing vacuum				
	[007502092] Plastic case for ZEROX M				