



# ZEROX M Dyno



LR9017.522-US-WW-350-827-SS



[WW]  
Wall-wash

## Configuration

|                       |               |
|-----------------------|---------------|
| Light distribution    | [WW] 35x28°   |
| Delivered lumens flux | 448 lm        |
| Rated input power     | 5 W           |
| Color temperature     | 2700 K CRI 80 |
| Luminaire efficacy    | 89 lm/W       |
| Lamp                  | 2 LED         |
| Color Deviation       | 3 SDCM        |
| Lifetime L90 (hour)   | >42,000       |
| Lifetime L80 (hour)   | >42,000       |

## Options

## Technical information

|                         |   |
|-------------------------|---|
| Mounting                | Ground recessed mountable   |
| Housing                 | Corrosion resistant stainless steel housing (AISI 316L / EN 1.4571 grade) |
| Fasteners               | Stainless steel (AISI 304 / EN 1.4301 grade)                              |
| Gasket                  | Silicone  |
| Lens / Reflector        | High reflectance aluminium coating, multifaceted micro reflector          |
| Glass / Diffusor        | Tempered safety glass   |
| Impact protection       | IK10  |
| Ingress protection      | IP67  |
| Input voltage           | 120-277V 50/60Hz  |
| Insulation class        | Class I   |
| Weight                  | 8.9 lbs   |
| LED module              | High power LEDs on metal-core PCB   |
| Driver                  | Internal LED driver   |
| Driver surge protection | 3/3 kV  |
| Power factor            | > 0.40  |
| Through wiring          | Single power cord entry   |
| Operating temperature   | -40...50°C  |
| Power cord              | 12" of rubber-sheated power cord  |

Accessories (Included)

Mounting accessories



Connector set - 5-pole

141407400

Accessories (To be ordered separately)

Mounting accessories



Case removing vacuum

160404012


Mounting accessories



Plastic case for ZEROX M

007502092

|                                |  |  |      |  |      |  |          |  |
|--------------------------------|--|--|------|--|------|--|----------|--|
| Project name                   |  |  |      |  | Type |  | Quantity |  |
| Date                           |  |  | Note |  |      |  |          |  |
| LR9017.522-US-WW-350-827-__-SS |  |  |      |  |      |  |          |  |

| Light distribution                           | Rated input power  | Color temperature   | Control                  | Product colors   |
|--|--|---|--------------------------|--|
| <b>[WW]</b><br>Wall-wash - 35x28°            | <b>[350]</b><br>5 W  | <b>[827]</b><br>2700 K CRI 80   | <b>[ONOFF]</b><br>On/Off | <b>[SS]</b><br>Stainless steel  |
|  |  | <b>[830]</b><br>3000 K CRI 80<br><b>[740]</b><br>4000 K CRI 70<br><b>[840]</b><br>4000 K CRI 80 | <b>[0-10V]</b><br>0-10V  |  |
| <b>Accessories (Included)</b>                | <b>Accessories (To be ordered separately)</b>  |   |                          |  |
| <b>Mounting accessories</b>                  | <b>Mounting accessories</b>  |   |                          |  |
| <b>[141407400]</b><br>Connector set - 5-pole | <b>[160404012]</b><br>Case removing vacuum<br><b>[007502092]</b><br>Plastic case for ZEROX M |   |                          |  |