


LB6053.509-US-SYM-3L-700-830



۲

[SYM-3L] Symmetric, Special effect: 3 lines

Configuration

Light distribution	[SYM-3L] 38x117°
Delivered lumens flux	1586 lm
Rated input power	29 W
Color temperature	3000 K CRI 80
Luminaire efficacy	56 lm/W
Lamp	3 LED
Color Deviation	4 SDCM
Lifetime L90 (hour)	>72,600
Lifetime L80 (hour)	>72,600


Options

Technical information

Housing	Corrosion resistant, marine grade aluminum
	housing
Finishing	Chromate conversion pretreatment followed by
	electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Liquid silicone
Lens / Reflector	PMMA lens with high optical efficiency
Glass / Diffusor	Tempered safety glass
Impact protection	IK05
Ingress protection	IP65
Input voltage	120-277V 50/60Hz
Insulation class	Class I
Weight	89.5 lbs
LED module	Multi-chip high power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge	6/6 kV
protection	
Power factor	> 0.95
Through wiring	Single power cord entry
Operating	-4050°C
temperature	

HEPER USA LLC W227 N546 Westmound Drive Waukesha, 53186 Wisconsin, United States +1 312 910 9740 infoUS@hepergroup.com

Accessories (To be ordered separately)



HEPER USA LLC W227 N546 Westmound Drive Waukesha, 53186 Wisconsin, United States +1 312 910 9740 infoUS@hepergroup.com We reserve the right to change specifications without prior written notice. Edition: 10.05.2024. For current version visit heperlighting.com. All flux (\pm %7 tolerance) and power values (\pm %10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

Project na	me			Туре	Quantity
Date		Note			
LB6053.	509-US-S`	YM-3L-70	0-830		

Light distribution	Rated input power	Color temperature	Control	Product colors
[SYM-3L] Symmetric, Special	[700] 29 W	[830] 3000 K CRI 80	[ONOFF] On/Off	[HM1] Black
effect: 3 lines - 38x117°	[1050] 42 W	[827] 2700 K CRI 80	[0-10V] 0-10V	[HM2] Dark gray
		[740] 4000 K CRI 70		[HM3] Anthracite gray
		[840] 4000 K CRI 80		[HM4] Light gray
				[HM5] White
				[HM6] Bronze
				[CC] (Section Color (Please specify RAL code)
Extras	Accessories (<i>To be</i> ordered separately)	_		
Luminaire body	Anchor bolts			
options [DPC] Double powder coating	[90CJ003] 90CJ003			
	Bolt covers			
	[C1J2K] C1J2K			