



LB6058.694-EN-SYM-1050-840



[SYM]
Symmetric

Configuration

Light distribution	[SYM] 98°
Delivered lumens flux	2700 lm
Rated input power	40 W
Color temperature	4000 K CRI 80
Luminaire efficacy	67 lm/W
Lamp	3 LED
Color Deviation	5 SDCM
Lifetime L90 (hour)	>72,600
Lifetime L80 (hour)	>72,600

Options

Technical information


Housing	Corrosion resistant, die-cast, marine grade aluminum housing
Finishing	Chromate conversion pretreatment followed by electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone
Lens / Reflector	High reflectance aluminium coating
Glass / Diffusor	Tempered safety glass
Impact protection	IK07
Ingress protection	IP65
Input voltage	220-240V 50/60Hz
Insulation class	Class I
Weight	19.87 kg (3 m), 23.61 kg (4 m)
LED module	Multi-chip high power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge protection	6/6 kV
Power factor	> 0.95
Through wiring	Single power cord entry
Operating temperature	-40...50°C
Pole detail	Poles are supplied with flange plate. Flange cover and anchorage can be ordered separately. Embedded base is optional

Notes

Please contact the sales department regarding this product's availability.


Accessories (To be ordered separately)

Optical accessories




Hat for VLORA
100817064

Anchor bolts




90CJ004
90CJ004

Base plates



F0603B
F0603B

Bolt covers



C1F2C
C1F2C

Project name					Type		Quantity	
Date			Note					
LB6058.694-EN-SYM-1050-840-__-__-__-__								

Light distribution	Rated input power	Color temperature	Control	Product colors	
[SYM] Symmetric - 98°	[1050] 40 W	[840] 4000 K CRI 80	[ONOFF] On/Off	[HM1] Black	
	[700] 26 W	[827] 2700 K CRI 80	[DALI] DALI	[HM2] Dark gray	
		[830] 3000 K CRI 80		[HM3] Anthracite gray	
		[740] 4000 K CRI 70		[HM4] Light gray	
		[HM5] White			
		[HM6] Bronze			
		[CC] Custom color (Please specify RAL code)			
Height	Extras	Accessories (<i>To be ordered separately</i>)			
[H3] 10' [H4] 13.1' [HC]	Consult the factory	Optical accessories			
	[UNI] 120-277V 50/60Hz	[100817064] Hat for VLORA			
	Luminaire body options	Anchor bolts			
		[90CJ004] 90CJ004			
	[DPC] Double powder coating	Base plates			
		[F0603B] F0603B			
		Bolt covers			
[C1F2C] C1F2C					