




NOX 96 LED



LT1010.765-EN-T-CB-A-500-730-SS



[T-CB-A]

Tunnel, Counter
beam, Type A

Configuration

Light distribution	[T-CB-A]
Delivered lumens flux	20428 lm
Rated input power	145 W
Color temperature	3000 K CRI 70
Luminaire efficacy	140 lm/W
Lamp	96 LED
Color Deviation	3 SDCM
Lifetime L90 (hour)	>102,000
Lifetime L80 (hour)	>102,000


Options

Technical information

Mounting	Standard strap connection.
Housing	Corrosion resistant stainless steel housing (AISI 316 / EN 1.4401 grade) combined with aluminum alloy heatsink
Finishing	Polished stainless steel , anodized aluminum
Fasteners	Stainless steel (AISI 316 / EN 1.4401 grade)
Gasket	EPDM gasket (Shore A 25-30)
Lens / Reflector	PMMA lens with high optical efficiency
Glass / Diffuser	Tempered safety glass
Impact protection	IK10
Ingress protection	IP66
Input voltage	220-240V 50/60Hz
Insulation class	Class I
Weight	10.50 kg
LED module	High power LEDs on metal-core PCB
Driver	External LED driver
Through wiring	Single power cord entry
Operating temperature	-40...50°C
Power cord	40" of halogen-free power cord

Accessories (To be ordered separately)

Mounting accessories	Mounting accessories	Mounting accessories
		
Control gear box S for NOX family	Control gear box M for NOX family	Control gear box L for NOX family
007502100	007502102	007502104

Mounting accessories

Preassembled cables and 5-pole connector set for NOX
007502168

Project name					Type		Quantity	
Date			Note					
LT1010.765-EN-T-CB-A-500-730-__-SS-__-__								

Light distribution	Rated input power	Color temperature	Control	Product colors
[T-CB-A] Tunnel, Counter beam, Type A	[500] 145 W	[730] 3000 K CRI 70		[SS] Stainless steel
[T-ASYM-A] Tunnel, Asymmetric, Type A	[700] 204 W	[740] 4000 K CRI 70		
[T-ASYM-B] Tunnel, Asymmetric, Type B	[350] 103 W			
[T-CB-D] Tunnel, Counter beam, Type D				
[T-CB-E] Tunnel, Counter beam, Type E				
[T-SYM-A] Tunnel, Symmetric, Type A				
[T-SYM-B] Tunnel, Symmetric, Type B				
Extras	Accessories (<i>To be ordered separately</i>)			
Light output	Mounting accessories			
[CLO] Constant light output	[007502100] Control gear box S for NOX family			
Consult the factory	[007502102] Control gear box M for NOX family			
[C2] Class II	[007502104] Control gear box L for NOX family			
[UNI] 120-277V 50/60Hz	[007502168] Preassembled cables and 5-pole connector set for NOX			