



LW8034.003-EN-MN-940-ONOFF-EN-C1



[N]
Narrow

Variant

Light distribution	[N] 25°
Delivered lumens flux	410 lm
Rated input power	7.5 W
Colour temperature	4000 K CRI 90
Luminaire efficacy	55 lm/W
Lamp	1 LAMP
MacAdam Ellipse	5 SDCM
BUG rating	B1-U0-G0

Options

Technical information

Mounting	Wall mountable
Housing	Corrosion resistant, marine grade aluminum housing
Finishing	Chromate conversion pretreatment followed by electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone
Glass / Diffusor	Tempered safety glass
Impact protection	IK06
Ingress protection	IP65
Input voltage	220-240V 50/60Hz
Insulation class	Class I
Weight	0.71 kg
Driver	Internal LED driver
Power factor	> 0.80
Through wiring	Single cable entry
Cable	0.2 m of flexible cable
Packing box dimensions	11*18*7 cm

Project name				Type		Quantity	
Date		Note					
LW8034.003-EN-MN-940-ONOFF-EN-C1-__-__							
Light distribution	Rated input power	Colour temperature	Control	Product colours			
[N] Narrow - 25° [VN] Very narrow - 10° [MN] Medium narrow - 36° [M] Medium - 60°	[I] 7.5 W	[940] 4000 K CRI 90 [927] 2700 K CRI 90 [930] 3000 K CRI 90	[ONOFF] On/Off	[HM1]  Black [HM2]  Dark grey [HM3]  Anthracite grey [HM4]  Light grey [HM5]  White [HM6]  Bronze [CC]  Custom colour (Please specify RAL code)			
Extras							
Consult the factory							
[UNI] 120-277V 50/60Hz							