



SPARK ST Duo

CE UK CA IK07 IP66



LB8044.529-EN-M-500-927-CC-36V-500-C3



[M]
Medium

Variant

Light distribution	[M] 60°
Delivered lumens flux	1570 lm
Rated input power	22 W
Colour temperature	2700 K CRI 90
Luminaire efficacy	78 lm/W
Lamp	2 LED
MacAdam Ellipse	3 SDCM
BUG rating	B1-U0-G0
Lifetime L90B50 (hour)	>50000
Lifetime L80B50 (hour)	>50000


Options

Technical information

Mounting	Surface mountable
Tilt angle	+90°/0°
Rotation angle	0°/+355°
Housing	Corrosion resistant, marine grade aluminum housing
Finishing	Knurled surface in black anodized aluminum and body in chromate conversion pretreatment followed by electrostatic powder coating
Fasteners	Stainless steel (AISI 316L)
Gasket	EPDM gasket (Shore A 25-30)
Lens / Reflector	PMMA lens with high optical efficiency
Glass / Diffusor	Tempered safety glass
Impact protection	IK07
Ingress protection	IP66
Input voltage	36 Vdc (Max) 500 mA
Insulation class	Class III
Weight	1.8 kg
LED module	High efficacy COB LED with long time reliability
Driver	External LED driver
Through wiring	Single cable entry
Operating temperature	-40...50°C
Cable	0.4 m of flexible cable
Notes	For 3000K 90CRI enquiries, please consult the factory.

Accessories (To be ordered separately)

Optical accessories



Visor for SPARK

101652204

Optical accessories



Snoot for SPARK

101652202


Mounting accessories



**DALI & On/Off
driver within an
IP67 box for
SPARK Duo**

007502122

Anchorage



628I004

628I004

Project name		Type		Quantity	
Date		Note			
LB8044.529-EN-M-500-927-__-CC-36V-500-C3-__-__-__-__					

Light distribution	Rated input power	Colour temperature	Control	Product colours
[M] Medium - 60° [VN] Very narrow - 18° [N] Narrow - 24° [MN] Medium narrow - 36°	[500] 22 W	[927] 2700 K CRI 90 [830] 3000 K CRI 80 [930] 3000 K CRI 90		[HM1]  Black [HM2]  Dark grey [HM3]  Anthracite grey [HM4]  Light grey [HM5]  White [HM6]  Bronze [CC]  Custom colour (Please specify RAL code)
Height	Extras	Accessories (<i>To be ordered separately</i>)		
[H0.60] 60cm [H0.90] 90cm [HC]	Light output [BCF] Blue Colour Filter [GCF] Green Colour Filter [HNY] Honeycomb [OCF] Orange Colour Filter [RCF] Red Colour Filter [YCF] Yellow Colour Filter Luminaire body options [DPC] Double powder coating	Optical accessories [101652204] Visor for SPARK [101652202] Snoot for SPARK Mounting accessories [007502122] DALI & On/Off driver within an IP67 box for SPARK Duo Anchorage [628I004] 628I004		