


PUNTO L

heper t

LF8019.698-EN-S-700-830









[S] Spot - NEMA Type 0

Configuration

Light distribution [S] 7° Delivered lumens flux 5884 lm Rated input power 60 W **Color temperature** 3000 K CRI 80 **Luminaire efficacy** 101 lm/W Lamp 7 LED **Color Deviation** 5 SDCM >72,600 Lifetime L90 (hour) Lifetime L80 (hour) >72,600

Options

Technical information

Mounting Yoke mount (standard), stake mount (optional) Tilt angle +60°/-30° Housing Corrosion resistant, die-cast, marine grade aluminum housing Finishing Chromate conversion pretreatment followed by electrostatic powder coating Fasteners Stainless steel (AISI 304 / EN 1.4301 grade) Gasket Silicone rubber Lens / Reflector High reflectance aluminium coating [S] [N], PMMA lens with high optical efficiency [MN] [M] Glass / Diffusor Tempered safety glass Impact protection **IK08** Ingress protection IP65 Input voltage 220-240V 50/60Hz **Insulation class** Class I Wind catching area 0.03 m² (EPA)

Weight 6.56 kg

LED module Multi-chip high power LEDs on metal-core PCB

Driver Internal LED driver

Driver surge 8/6 kV

protection

Power factor > 0.98
Through wiring Single power cord entry
Operating -40...50°C

temperature

Power cord 16" of flexible power cord

Accessories (To be ordered separately)

Optical accessories

Mounting accessories





Snoot for PUNTO L

007502177

Spike 160405040

Project name					Туре	Quantity	
Date			Note				

LF8019.698-EN-S-700-830-__--__-

Light distribution	Rated input power	Color temperature	Control	Product colors	
[S] Spot - NEMA Type 0 - 7°	[700] 60 W	[830] 3000 K CRI 80	[ONOFF] On/Off	[HM1] Black	
[N] Narrow - NEMA Type 2 - 26°		[827] 2700 K CRI 80 [740] 4000 K CRI 70	[DALI] DALI	[HM2] Dark gray [HM3]	
[MN] Medium narrow - NEMA Type 3 - 42°		[840] 4000 K CRI 80		Anthracite gray [HM4] Light gray	
[M] Medium - NEMA Type 4 - 60°				[HM5] White	
				[HM6] Bronze	
				[CC] Custom color (Please specify RAL code)	
Extras	Accessories (To be ordered separately)				
Consult the factory	Optical accessories				
[UNI] 120-277V 50/60Hz	[007502177] Snoot for PUNTO L				
Luminaire body options	Mounting accessories				
[DPC] Double powder coating	[160405040] Spike				