


LD8017.693-EN-M-700-827-ONOFF-EN-C1



[S] [N]

[MN] [M]



[M]

Medium

Variant

Light distribution	[M] 60°
Delivered lumens flux	606 lm
Rated input power	10 W
Colour temperature	2700 K CRI 80
Luminaire efficacy	60 lm/W
Lamp	1 LED
MacAdam Ellipse	5 SDCM
BUG rating	B1-U0-G0
Lifetime L90B50 (hour)	>72,600
Lifetime L80B50 (hour)	>72,600

Options

Technical information

Mounting	Ceiling mountable
Housing	Corrosion resistant, die-cast, marine grade aluminum housing
Finishing	Chromate conversion pretreatment followed by electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone rubber
Lens / Reflector	High reflectance aluminium coating [S] [N], PMMA lens with high optical efficiency [MN] [M]
Glass / Diffuser	Tempered safety glass
Impact protection	IK08
Ingress protection	IP65
Input voltage	220-240V 50/60Hz
Insulation class	Class I
Weight	1.16 kg
LED module	Multi-chip high power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge protection	1/1 kV
Power factor	> 0.91
Through wiring	Single cable entry
Operating temperature	-25...50°C
Cable	0.2 m of flexible cable

Accessories (To be ordered separately)

Optical accessories



Visor for PUNTO S

007502282

Project name					Type		Quantity	
Date			Note					
LD8017.693-EN-M-700-827-ONOFF-EN-C1-__-__								

Light distribution	Rated input power	Colour temperature	Control	Product colours	
[M] Medium - 60°	[700] 10 W	[827] 2700 K CRI 80	[ONOFF] On/Off	[HM1] Black	
[S] Spot - 7°		[830] 3000 K CRI 80		[HM2] Dark grey	
[N] Narrow - 26°		[740] 4000 K CRI 70		[HM3] Anthracite grey	
[MN] Medium narrow - 42°		[840] 4000 K CRI 80		[HM4] Light grey	
				[HM5] White	
				[HM6] Bronze	
				[CC] Custom colour (Please specify RAL code)	
Extras	Accessories (<i>To be ordered separately</i>)				
Consult the factory	Optical accessories				
[UNI] 120-277V 50/60Hz	[007502282] Visor for PUNTO S				