


LD8017.693-EN-M-700-830-ONOFF-EN-C1



[M]  
Medium

## Variant

|                        |               |
|------------------------|---------------|
| Light distribution     | [M] 60°       |
| Delivered lumens flux  | 615 lm        |
| Rated input power      | 10 W          |
| Colour temperature     | 3000 K CRI 80 |
| Luminaire efficacy     | 61 lm/W       |
| Lamp                   | 1 LED         |
| MacAdam Ellipse        | 5 SDCM        |
| BUG rating             | B1-U0-G0      |
| Lifetime L90B50 (hour) | >72,600       |
| Lifetime L80B50 (hour) | >72,600       |

## Options

## Technical information

|                         |                                                                                             |
|-------------------------|---------------------------------------------------------------------------------------------|
| Mounting                | Ceiling mountable                                                                           |
| Housing                 | Corrosion resistant, die-cast, marine grade aluminum housing                                |
| Finishing               | Chromate conversion pretreatment followed by electrostatic powder coating                   |
| Fasteners               | Stainless steel (AISI 304 / EN 1.4301 grade)                                                |
| Gasket                  | Silicone rubber                                                                             |
| Lens / Reflector        | High reflectance aluminium coating [S] [N], PMMA lens with high optical efficiency [MN] [M] |
| Glass / Diffusor        | Tempered safety glass                                                                       |
| Impact protection       | IK08                                                                                        |
| Ingress protection      | IP65                                                                                        |
| Input voltage           | 220-240V 50/60Hz                                                                            |
| Insulation class        | Class I                                                                                     |
| Weight                  | 1.16 kg                                                                                     |
| LED module              | Multi-chip high power LEDs on metal-core PCB                                                |
| Driver                  | Internal LED driver                                                                         |
| Driver surge protection | 1/1 kV                                                                                      |
| Power factor            | > 0.91                                                                                      |
| Through wiring          | Single cable entry                                                                          |
| Operating temperature   | -25...50°C                                                                                  |
| Cable                   | 0.2 m of flexible cable                                                                     |

## Accessories (To be ordered separately)

---

### Optical accessories



#### Visor for PUNTO S

007502282

|              |  |      |  |          |  |
|--------------|--|------|--|----------|--|
| Project name |  | Type |  | Quantity |  |
| Date         |  | Note |  |          |  |

**LD8017.693-EN-M-700-830-ONOFF-EN-C1-\_\_-\_\_**

| Light distribution                 | Rated input power                                    | Colour temperature            | Control                  | Product colours                                                                                                                            |
|------------------------------------|------------------------------------------------------|-------------------------------|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| <b>[M]</b><br>Medium - 60°         | <b>[700]</b><br>10 W                                 | <b>[830]</b><br>3000 K CRI 80 | <b>[ONOFF]</b><br>On/Off | <b>[HM1]</b><br>Black                                   |
| <b>[S]</b><br>Spot - 7°            |                                                      | <b>[827]</b><br>2700 K CRI 80 |                          | <b>[HM2]</b><br>Dark grey                               |
| <b>[N]</b><br>Narrow - 26°         |                                                      | <b>[740]</b><br>4000 K CRI 70 |                          | <b>[HM3]</b><br>Anthracite grey                         |
| <b>[MN]</b><br>Medium narrow - 42° |                                                      | <b>[840]</b><br>4000 K CRI 80 |                          | <b>[HM4]</b><br>Light grey                              |
|                                    |                                                      |                               |                          | <b>[HM5]</b><br>White                                   |
|                                    |                                                      |                               |                          | <b>[HM6]</b><br>Bronze                                  |
|                                    |                                                      |                               |                          | <b>[CC]</b> <br>Custom colour (Please specify RAL code) |
| <b>Extras</b>                      | <b>Accessories (<i>To be ordered separately</i>)</b> |                               |                          |                                                                                                                                            |
| <b>Consult the factory</b>         | <b>Optical accessories</b>                           |                               |                          |                                                                                                                                            |
| <b>[UNI]</b><br>120-277V 50/60Hz   | <b>[007502282]</b><br>Visor for PUNTO S              |                               |                          |                                                                                                                                            |