


## LF8019.698-US-N-700-827



126 mm 4 61/64" 166 mm 6 17/32 Ø229 mm Ø9 1/64"



267 mm 10 33/64"

[N] Narrow - NEMA Type 2

## Configuration

Light distribution	[N] 26°
Delivered lumens flux	5797 lm
Rated input power	60 W
Color temperature	2700 K CRI 80
Luminaire efficacy	99 lm/W
Lamp	7 LED
Color Deviation	5 SDCM
Lifetime L90 (hour)	>72,600
Lifetime L80 (hour)	>72,600

#### Options

### Technical information

Mounting	Yoke mount (standard), stake mount (optional)
Tilt angle	+60°/-30°
Housing	Corrosion resistant, die-cast, marine grade
	aluminum housing
Finishing	Chromate conversion pretreatment followed by
	electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone rubber
Lens / Reflector	High reflectance aluminium coating [S] [N],
	PMMA lens with high optical efficiency [MN] [M]
Glass / Diffusor	Tempered safety glass
Impact protection	IK08
Ingress protection	IP65
Input voltage	120-277V 50/60Hz
Insulation class	Class I
Wind catching area	0.33 ft²
(EPA)	
Weight	14.4 lbs
LED module	Multi-chip high power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge	10/6 kV
protection	
Power factor	> 0.97
Through wiring	Single power cord entry
Operating	-3050°C
temperature	
Power cord	16" of flexible power cord

HEPER USA LLC W227 N546 Westmound Drive Waukesha, 53186 Wisconsin, United States +1 312 910 9740 infoUS@hepergroup.com

We reserve the right to change specifications without prior written notice. Edition: 17.05.2024. For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

# Accessories (To be ordered separately)



007502177

160405040

HEPER USA LLC W227 N546 Westmound Drive Waukesha, 53186 Wisconsin, United States +1 312 910 9740 infoUS@hepergroup.com We reserve the right to change specifications without prior written notice. Edition: 17.05.2024. For current version visit heperlighting.com. All flux ( $\pm$ %7 tolerance) and power values ( $\pm$ %10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

Project na	me			Туре	Quantity		
Date	Date		Note				
LF8019.	598-US-N	-700-827	·				

			Product colors
<b>[700]</b> 60 W	<b>[827]</b> 2700 K CRI 80	<b>[ONOFF]</b> On/Off	[HM1] Black
	<b>[830]</b> 3000 K CRI 80	<b>[0-10V]</b> 0-10V	[HM2] Dark gray
	<b>[740]</b> 4000 K CRI 70		[HM3] Anthracite gray
	<b>[840]</b> 4000 K CRI 80		[HM4] Light gray
			<b>[HM5]</b> White
			[HM6] Bronze
			[CC] Sustom color (Pleas specify RAL code)
Accessories (To be ordered separately)			
Optical accessories			
[007502177] Snoot for PUNTO L			
Mounting accessories			
<b>[160405040]</b> Spike			
	60 W Accessories ( <i>To be</i> ordered separately) Optical accessories [007502177] Snoot for PUNTO L Mounting accessories [160405040]	60 W  2700 K CRI 80    [830]  3000 K CRI 80    [740]  4000 K CRI 70    [840]  4000 K CRI 80    4000 K CRI 80  4000 K CRI 80    Accessories (To be ordered separately)  9    Optical accessories  [007502177]    Snoot for PUNTO L  Mounting accessories    [160405040]	60 W    2700 K CRI 80    On/Off      [830]    3000 K CRI 80    0-10V      [740]    4000 K CRI 70    0-10V      [840]    4000 K CRI 80    0      4000 K CRI 80    0    0      [007502177]    Snoot for PUNTO L    0      Mounting accessories    [160405040]    0