


## LF8019.698-US-S-700-827





267 mm 10 33/64"

[S] Spot - NEMA Type 0

## Configuration

Light distribution	[S] 7°
Delivered lumens flux	5797 lm
Rated input power	60 W
Color temperature	2700 K CRI 80
Luminaire efficacy	99 lm/W
Lamp	7 LED
Color Deviation	5 SDCM
Lifetime L90 (hour)	>72,600
Lifetime L80 (hour)	>72,600

#### Options

### Technical information

Mounting	Yoke mount (standard), stake mount (optional)
Tilt angle	+60°/-30°
Housing	Corrosion resistant, die-cast, marine grade
	aluminum housing
Finishing	Chromate conversion pretreatment followed by
	electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone rubber
Lens / Reflector	High reflectance aluminium coating [S] [N],
	PMMA lens with high optical efficiency [MN] [M]
Glass / Diffusor	Tempered safety glass
Impact protection	IK08
Ingress protection	IP65
Input voltage	120-277V 50/60Hz
Insulation class	Class I
Wind catching area	0.33 ft²
(EPA)	
Weight	14.4 lbs
LED module	Multi-chip high power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge	10/6 kV
protection	
Power factor	> 0.97
Through wiring	Single power cord entry
Operating	-3050°C
temperature	
Power cord	16" of flexible power cord
	•

HEPER USA LLC W227 N546 Westmound Drive Waukesha, 53186 Wisconsin, United States +1 312 910 9740 infoUS@hepergroup.com

# Accessories (To be ordered separately)



007502177

160405040

HEPER USA LLC W227 N546 Westmound Drive Waukesha, 53186 Wisconsin, United States +1 312 910 9740 infoUS@hepergroup.com We reserve the right to change specifications without prior written notice. Edition: 17.05.2024. For current version visit heperlighting.com. All flux ( $\pm$ %7 tolerance) and power values ( $\pm$ %10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

Project na	me			Туре	Quantity	
Date			Note			
LF8019.	598-US-S-	700-827-				

Rated input power	Color temperature	Control	Product colors
<b>[700]</b> 60 W	<b>[827]</b> 2700 K CRI 80	<b>[ONOFF]</b> On/Off	[HM1] Black
	<b>[830]</b> 3000 K CRI 80	<b>[0-10V]</b> 0-10V	[HM2] Dark gray
	<b>[740]</b> 4000 K CRI 70		[HM3] Anthracite gray
	<b>[840]</b> 4000 K CRI 80		[HM4] Light gray
			<b>[HM5]</b> White
			[HM6] Bronze
			<b>[CC]</b> Custom color (Pleas specify RAL code)
Accessories (To be ordered separately)			
Optical accessories			
[007502177] Snoot for PUNTO L			
Mounting accessories			
<b>[160405040]</b> Spike			
	[700]   60 W   60 W   Accessories (To be ordered separately)   Optical accessories   [007502177]   Snoot for PUNTO L   Mounting accessories   [160405040]	[700] [827]   60 W [830]   3000 K CRI 80 [740]   4000 K CRI 70 [840]   4000 K CRI 80 [900]   4000 K CRI 80 [900]   Accessories (To be ordered separately) [907502177]   Optical accessories [007502177]   Snoot for PUNTO L Mounting accessories   [160405040] [160405040]	[700]   [827]   [ONOFF]     60 W   2700 K CRI 80   [0.10V]     3000 K CRI 80   [0.10V]     3000 K CRI 70   [840]     4000 K CRI 70   [840]     4000 K CRI 80   -10V     4000 K CRI 80   -10V     60 W   -10V     100 K CRI 80   -10V     900 K CRI 80   -10V     100 K CRI 80   -10V     900 K CRI 80   -10V