

#### **PUNTO S**

# heper "

#### LF8017.693-US-M-700-827









**[M]** Medium - NEMA Type 4

### Configuration

**Light distribution** [M] 60° **Delivered lumens flux** 606 lm 10 W Rated input power **Color temperature** 2700 K CRI 80 **Luminaire efficacy** 60 lm/W Lamp 1 LED **Color Deviation** 5 SDCM Lifetime L90 (hour) >72,600 Lifetime L80 (hour) >72,600

#### Options

#### Technical information

recillical lillorill	ation
Mounting	Yoke mount (standard), stake mount (optional)
Tilt angle	+60°/-30°
Housing	Corrosion resistant, die-cast, marine grade
	aluminum housing
Finishing	Chromate conversion pretreatment followed by
	electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone rubber
Lens / Reflector	High reflectance aluminium coating [S] [N],
	PMMA lens with high optical efficiency [MN] [M]
Glass / Diffusor	Tempered safety glass
Impact protection	IK08
Ingress protection	IP65
Input voltage	120-277V 50/60Hz
Insulation class	Class I
Wind catching area	0.23 ft²
(EPA)	
Weight	3.3 lbs
LED module	Multi-chip high power LEDs on metal-core PCB

 LED module
 Multi-chip high power LEDs on metal-core PCB

 Driver
 Internal LED driver

 Driver surge
 1/1 kV

 protection

Power factor > 0.90
Through wiring Single power cord entry
Operating -30...50°C

temperature

**Power cord** 16" of flexible power cord

## Accessories (To be ordered separately)

Optical accessories

Mounting accessories





Visor for PUNTO S

007502282

**Spike** 160405040

Project na	me		Туре	Quantity	
Date		Note			

## LF8017.693-US-M-700-827-\_\_--\_

Light distribution	Rated input power	Color temperature	Control	Product colors
[M] Medium - NEMA Type	[ <b>700]</b> 10 W	[ <b>827</b> ] 2700 K CRI 80	[ONOFF] On/Off	[HM1] Black
4 - 60°  [S] Spot - NEMA Type 0 - 7°  [N]		[ <b>830]</b> 3000 K CRI 80	<b>[0-10V]</b> 0-10V	[HM2] Dark gray
		[ <b>840]</b> 4000 K CRI 80		[HM3] Anthracite gray
Narrow - NEMA Type 2 - 26°				[HM4] Light gray
[MN] Medium narrow - NEMA Type 3 - 42°				[HM5] White
71				[HM6] Bronze
				[CC] Custom color (Please specify RAL code)
Extras	Accessories (To be ordered separately)			
Luminaire body	Optical accessories			
[DPC] Double powder coating	[007502282] Visor for PUNTO S			
	Mounting accessories			
	[ <b>160405040</b> ] Spike	_		