

## **PUNTO S**

# **heper**

#### LF8017.693-US-MN-700-830









[MN] Medium narrow -NEMA Type 3

#### Configuration

**Light distribution** [MN] 42° Delivered lumens flux 697 lm Rated input power 10 W **Color temperature** 3000 K CRI 80 **Luminaire efficacy** 69 lm/W Lamp 1 LED **Color Deviation** 5 SDCM >72,600 Lifetime L90 (hour) Lifetime L80 (hour) >72,600

## Options

#### Technical information

Mounting Yoke mount (standard), stake mount (optional) Tilt angle +60°/-30° Housing Corrosion resistant, die-cast, marine grade aluminum housing Finishing Chromate conversion pretreatment followed by electrostatic powder coating Fasteners Stainless steel (AISI 304 / EN 1.4301 grade) Gasket Silicone rubber Lens / Reflector High reflectance aluminium coating [S] [N], PMMA lens with high optical efficiency [MN] [M] Glass / Diffusor Tempered safety glass Impact protection **IK08** Ingress protection IP65 Input voltage 120-277V 50/60Hz **Insulation class** Class I Wind catching area 0.23 ft<sup>2</sup> (EPA) Weight 3.3 lbs

Weight 3.3 lbs
LED module Multi-chip high power LEDs on metal-core PCB
Driver Internal LED driver
Driver surge 1/1 kV

protection

Power factor > 0.90

Through wiring Single power cord entry

Operating temperature

and applicable standards.

**Power cord** 16" of flexible power cord

-30...50°C

# Accessories (To be ordered separately)

Optical accessories

Mounting accessories





Visor for PUNTO S

007502282

**Spike** 160405040

Project name					Туре	Quantity	
Date			Note				

## LF8017.693-US-MN-700-830-\_\_--\_

Light distribution	Rated input power	Color temperature	Control	<b>Product colors</b>
[MN] Medium narrow -	[ <b>700]</b> 10 W	[830] 3000 K CRI 80	[ONOFF] On/Off	[HM1] Black
NEMA Type 3 - 42°  [S] Spot - NEMA Type 0 -		[ <b>827</b> ] 2700 K CRI 80	<b>[0-10V]</b> 0-10V	[HM2] Dark gray
7° [N]		[ <b>730]</b> 3000 K CRI 70		[HM3] Anthracite gray
Narrow - NEMA Type 2 - 26°		[740] 4000 K CRI 70 [840] 4000 K CRI 80		[HM4] Light gray
<b>[M]</b> Medium - NEMA Type 4 - 60°				[HM5] White
				[HM6] Bronze
				[CC] Custom color (Please specify RAL code)
Extras	Accessories (To be ordered separately)			
Luminaire body	Optical accessories			
options [DPC]	[007502282] Visor for PUNTO S			
Double powder coating	Mounting accessories			
	[ <b>160405040</b> ] Spike			