
PUNTO S W Duo









LW7036.519-US-N-N-700-830-UNI-C1









[N-N] Narrow (Up & Down)

Variant

Light distribution [N-N] 26° **Delivered lumens flux** 1698 lm Rated input power 18 W **Colour temperature** 3000 K CRI 80 **Luminaire efficacy** 84 lm/W Lamp 2 LED MacAdam Ellipse 5 SDCM B1-U0-G0 **BUG** rating Lifetime L90B50 (hour) >72,600 Lifetime L80B50 (hour) >72,600

Options

Technical information

rechnical inform	lauon
Mounting	Wall mountable
Housing	Corrosion resistant, marine grade aluminum
	housing
Finishing	Chromate conversion pretreatment followed by
	electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone rubber
Lens / Reflector	High reflectance aluminium coating [S] [N],
	PMMA lens with high optical efficiency [MN] [M]
Glass / Diffusor	Tempered safety glass
Impact protection	IK08
Ingress protection	IP65
Input voltage	120-277V 50/60Hz
Insulation class	Class I
Weight	3.3 lbs
LED module	Multi-chip high power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge	2/2 kV
protection	
Power factor	> 0.90
Through wiring	Single cable entry
Operating	-4050°C
temperature	
Cable	0.2 m of flexible cable

Accessories (To be ordered separately)

Optical accessories



Visor for PUNTO S

007502282

Project name			Туре	Quantity		
Date			Note			

LW7036.519-US-N-N-700-830-___-UNI-C1-__

Light distribution	Rated input power	Colour temperature	Control	Product colours
[N-N] Narrow (Up & Down) -	[700] 18 W	[830] 3000 K CRI 80	[ONOFF] On/Off	[HM1] Black
[S-S] Spot (Up & Down) - 7° [MN-MN] Medium Narrow (Up & Down) - 42° [M-M] Medium (Up & Down) - 60°		[827] 2700 K CRI 80 [740] 4000 K CRI 70 [840] 4000 K CRI 80	[0-10V] 0-10V	[HM2] Dark grey [HM3] Anthracite grey [HM4] Light grey [HM5] White [HM6] Bronze [CC] Custom colour (Please specify RAL code)

Accessories (To be ordered separately)

Optical accessories

[007502282]

Visor for PUNTO S