
PUNTO S W Duo









LW7036.519-US-S-S-700-740-UNI-C1









[S-S] Spot (Up & Down)

Variant

Light distribution [S-S] 7° **Delivered lumens flux** 2038 lm Rated input power 18 W **Colour temperature** 4000 K CRI 70 **Luminaire efficacy** 113 lm/W Lamp 2 LED MacAdam Ellipse 5 SDCM **BUG** rating B1-U1-G0 Lifetime L90B50 (hour) >72,600 Lifetime L80B50 (hour) >72,600

Options

Technical information

recillical illiorination						
Mounting	Wall mountable					
Housing	Corrosion resistant, marine grade aluminum					
	housing					
Finishing	Chromate conversion pretreatment followed by					
	electrostatic powder coating					
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)					
Gasket	Silicone rubber					
Lens / Reflector	High reflectance aluminium coating [S] [N],					
	PMMA lens with high optical efficiency [MN] [M]					
Glass / Diffusor	Tempered safety glass					
Impact protection	IK08					
Ingress protection	IP65					
Input voltage	120-277V 50/60Hz					
Insulation class	Class I					
Weight	3.3 lbs					
LED module	Multi-chip high power LEDs on metal-core PCB					
Driver	Internal LED driver					
Driver surge	2/2 kV					
protection						
Power factor	> 0.90					
Through wiring	Single cable entry					
Operating	-4050°C					
temperature						
Cable	0.2 m of flexible cable					
Notes	Please consult factory for combinations of					

Başkent OSB 22. Cd. No: 2, Malıköy, Temelli, Sincan, 06909 Ankara, Turkey +90 312 267 54 30 info@hepergroup.com

Hemer, Germany +49 237 2901 2975 infoEU@hepergroup.com We reserve the right to change specifications without prior written notice. Edition: 07.05.2024. For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

different light distributions.

Accessories (To be ordered separately)

Optical accessories



Visor for PUNTO S

007502282

Project na	name		Туре	Quantity			
Date			Note				

LW7036.519-US-S-S-700-740-___-UNI-C1-__

Light distribution	Rated input power	Colour temperature	Control	Product colours
[S-S] Spot (Up & Down) - 7°	[700] 18 W	[740] 4000 K CRI 70	[ONOFF] On/Off	[HM1] Black
[N-N] Narrow (Up & Down) - 26° [MN-MN] Medium Narrow (Up & Down) - 42° [M-M] Medium (Up & Down) - 60°		[827] 2700 K CRI 80 [830] 3000 K CRI 80 [840] 4000 K CRI 80	[0-10V] 0-10V	[HM2] Dark grey [HM3] Anthracite grey [HM4] Light grey [HM5] White [HM6] Bronze [CC] Custom colour (Please specify RAL code)

Accessories (To be ordered separately)

Optical accessories

[007502282]

Visor for PUNTO S