
PUNTO S W Duo



LW7036.519-US-S-5-700-740





120' Gamma Angles 180' 120' 109' 5000 100' 75' 5000 75' 45' 25000 45' 45' 45' 30' 15' 0' 15' 30'



Spot - NEMA Type 0 (Up & Down)

Configuration

Light distribution	[S-S] 7°
Delivered lumens flux	2038 lm
Rated input power	18 W
Color temperature	4000 K CRI 70
Luminaire efficacy	113 lm/W
Lamp	2 LED
Color Deviation	5 SDCM
BUG rating	B1-U1-G0
Lifetime L90 (hour)	>72,600
Lifetime L80 (hour)	>72,600

Options

Notes

Technical information

Mounting	Wall mountable
Housing	Corrosion resistant, marine grade aluminum
	housing
Finishing	Chromate conversion pretreatment followed by
	electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone rubber
Lens / Reflector	High reflectance aluminium coating [S] [N],
	PMMA lens with high optical efficiency [MN] [M]
Glass / Diffusor	Tempered safety glass
Impact protection	IK08
Ingress protection	IP65
Input voltage	120-277V 50/60Hz
Insulation class	Class I
Weight	3.3 lbs
LED module	Multi-chip high power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge	2/2 kV
protection	
Power factor	> 0.90
Through wiring	Single power cord entry
Operating	-4050°C
temperature	
Power cord	8" of flexible power cord

8" of flexible power cord Please consult factory for combinations of different beam spreads.

HEPER USA LLC W227 N546 Westmound Drive Waukesha, 53186 Wisconsin, United States +1 312 910 9740 infoUS@hepergroup.com We reserve the right to change specifications without prior written notice. Edition: 03.05.2024. For current version visit heperlighting.com. All flux (\pm %7 tolerance) and power values (\pm %10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

Accessories (To be ordered separately)

Optical accessories



Visor for PUNTO S

007502282

HEPER USA LLC W227 N546 Westmound Drive Waukesha, 53186 Wisconsin, United States +1 312 910 9740 infoUS@hepergroup.com We reserve the right to change specifications without prior written notice. Edition: 03.05.2024. For current version visit heperlighting.com. All flux (\pm %7 tolerance) and power values (\pm %10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

Project na	me			Туре	Quantity		
Date			Note				
LW7036	.519-US-S	5-S-700-74	40				

Light distribution	Rated input power	Color temperature	Control	Product colors
[S-S] Spot - NEMA Type 0	[700] 18 W	[740] 4000 K CRI 70	[ONOFF] On/Off	[HM1] Black
(Up & Down) - 7° [N-N] Narrow - NEMA Type		[827] 2700 K CRI 80 [830]	[0-10V] 0-10V	[HM2] Dark gray
2 (Up & Down) - 26° [MN-MN]		3000 K CRI 80		[HM3] Anthracite gray
Medium Narrow (Up & Down) - 42°		[840] 4000 K CRI 80		[HM4] Light gray
[M-M] Medium (Up & Down) - 60°				[HM5] White
				[HM6] Bronze
				[CC] (Please specify RAL code)
Accessories (To be ordered separately)				I

Optical accessories

[007502282] Visor for PUNTO S