


## **PUNTO S W Duo**

# heper "

#### LW7036.519-US-S-S-700-827









[S-S]
Spot - NEMA Type 0
(Up & Down)

## Configuration

**Light distribution** [S-S] 7° **Delivered lumens flux** 1678 lm Rated input power 18 W **Color temperature** 2700 K CRI 80 **Luminaire efficacy** 93 lm/W Lamp 2 LED **Color Deviation** 5 SDCM **BUG** rating B1-U0-G0 >72,600 Lifetime L90 (hour) Lifetime L80 (hour) >72,600

#### Options

#### Technical information

recillical illiorination						
Mounting	Wall mountable					
Housing	Corrosion resistant, marine grade aluminum					
	housing					
Finishing	Chromate conversion pretreatment followed by					
	electrostatic powder coating					
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)					
Gasket	Silicone rubber					
Lens / Reflector	High reflectance aluminium coating [S] [N],					
	PMMA lens with high optical efficiency [MN] [M]					
Glass / Diffusor	Tempered safety glass					
Impact protection	IK08					
Ingress protection	IP65					
Input voltage	120-277V 50/60Hz					
Insulation class	Class I					
Weight	3.3 lbs					
LED module	Multi-chip high power LEDs on metal-core PCB					
Driver	Internal LED driver					
Driver surge	2/2 kV					
protection						
Power factor	> 0.90					
Through wiring	Single power cord entry					
Operating	-4050°C					
temperature						
Power cord	8" of flexible power cord					
Notes	Please consult factory for combinations of					

Wisconsin, United States +1 312 910 9740 infoUS@hepergroup.com different beam spreads.

# Accessories (To be ordered separately)

Optical accessories



Visor for PUNTO S

007502282

Project na	me			Туре	Quantity		
Date			Note				

# LW7036.519-US-S-S-700-827-\_\_\_-

Light distribution	Rated input power	Color temperature	Control	Product colors
[S-S] Spot - NEMA Type 0	[ <b>700]</b> 18 W	[ <b>827]</b> 2700 K CRI 80	[ONOFF] On/Off	[HM1] Black
[N-N] Narrow - NEMA Type 2 (Up & Down) - 26° [MN-MN] Medium Narrow (Up & Down) - 42° [M-M] Medium (Up & Down) - 60°		[830] 3000 K CRI 80 [740] 4000 K CRI 70 [840] 4000 K CRI 80	[0-10V] 0-10V	[HM2] Dark gray  [HM3] Anthracite gray  [HM4] Light gray  [HM5] White  [HM6] Bronze  [CC] Custom color (Please specify RAL code)
				Bronze  [CC]  Custom color (Please

Accessories (To be ordered separately)

**Optical accessories** 

[007502282]

Visor for PUNTO S