


VEGA

LF8021.695-US-N-700-830









Narrow - NEMA Type 2

Configuration

Light distribution [N] 26° **Delivered lumens flux** 3397 lm Rated input power 35 W **Color temperature** 3000 K CRI 80 84 lm/W **Luminaire efficacy** 4 LED Lamp **Color Deviation** 5 SDCM Lifetime L90 (hour) >72,600 >72,600 Lifetime L80 (hour)

Options

Technical information

Mounting	Yoke mount (standard), stake mount (optional)
Tilt angle	+60°/-30°
Housing	Corrosion resistant, die-cast, marine grade
	aluminum housing
Finishing	Chromate conversion pretreatment followed by
	electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Liquid silicone
Lens / Reflector	High reflectance aluminium coating [S] [N],
	PMMA lens with high optical efficiency [MN] [M]
Glass / Diffusor	Tempered safety glass
Impact protection	IK07
Ingress protection	IP65
Input voltage	120-277V 50/60Hz
Insulation class	Class I
Wind catching area	0.40 ft ²
(EPA)	
Weight	14.3 lbs

LED module Multi-chip high power LEDs on metal-core PCB Driver Internal LED driver **Driver surge** 10/6 kV protection

Power factor > 0.95 Through wiring Single power cord entry

Operating temperature

We reserve the right to change specifications without prior

written notice. Edition: 02.05.2024. For current version visit

heperlighting.com. All flux (±%7 tolerance) and power values

(±%10 tolerance) are derived following appropriate IES, CIE,

and applicable standards.

Power cord 16" of flexible power cord

-40...50°C

Accessories (To be ordered separately)

Optical accessories

Mounting accessories





Visor for VEGA

Spike 160405040

Project na	me		Туре	Quantity	
Date		Note			

LF8021.695-US-N-700-830-___-_

Light distribution	Rated input power	Color temperature	Control	Product colors
[N] Narrow - NEMA Type	[700] 35 W	[830] 3000 K CRI 80	[ONOFF] On/Off	[HM1] Black
2 - 26° [S] Spot - NEMA Type 0 - 7°		[827] 2700 K CRI 80	[0-10V] 0-10V	[HM2] Dark gray
		[740] 4000 K CRI 70		[HM3] Anthracite gray
[MN] Medium narrow - NEMA Type 3 - 42°		[840] 4000 K CRI 80		[HM4] Light gray
[M] Medium - NEMA Type 4 - 60°				[HM5] White
				[HM6] Bronze
				Custom color (Pleas specify RAL code)
Extras	Accessories (To be ordered separately)			
Luminaire body	Optical accessories			
[DPC] Double powder coating	[100708017] Visor for VEGA			
	Mounting accessories			
	[160405040] Spike			