

### **VEGA**

# heper "

#### LF8021.695-US-MN-700-830









[MN] Medium narrow -NEMA Type 3

## Configuration

**Light distribution** [MN] 42° **Delivered lumens flux** 2747 lm 35 W Rated input power **Color temperature** 3000 K CRI 80 68 lm/W **Luminaire efficacy** 4 LED Lamp **Color Deviation** 5 SDCM Lifetime L90 (hour) >72,600 >72,600 Lifetime L80 (hour)

#### Options

#### Technical information

Mounting Tilt angle	Yoke mount (standard), stake mount (optional) +60°/-30°
Housing	Corrosion resistant, die-cast, marine grade aluminum housing
Finishing	Chromate conversion pretreatment followed by
	electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Liquid silicone
Lens / Reflector	High reflectance aluminium coating [S] [N],
	PMMA lens with high optical efficiency [MN] [M]
Glass / Diffusor	Tempered safety glass
Impact protection	IK07
Ingress protection	IP65
Input voltage	120-277V 50/60Hz
Insulation class	Class I
Wind catching area	0.40 ft <sup>2</sup>
(EPA)	
Weight	14.3 lbs

Weight 14.3 lbs
LED module Multi-chip high power LEDs on metal-core PCB
Driver Internal LED driver
Driver surge 10/6 kV

protection
Power factor > 0.95
Through wiring Single power cord entry

**Operating** -40...50°C

temperature

**Power cord** 16" of flexible power cord

heperlighting.com. All flux (±%7 tolerance) and power values

(±%10 tolerance) are derived following appropriate IES, CIE,

and applicable standards.

# Accessories (To be ordered separately)

Optical accessories

Mounting accessories





Visor for VEGA

**Spike** 160405040

Project na	me		Туре	Quantity	
Date		Note			

## LF8021.695-US-MN-700-830-\_\_--\_

Light distribution	Rated input power	Color temperature	Control	<b>Product colors</b>
[MN] Medium narrow -	[ <b>700]</b> 35 W	[ <b>830</b> ] 3000 K CRI 80	[ONOFF] On/Off	[HM1] Black
NEMA Type 3 - 42°  [S] Spot - NEMA Type 0 - 7°  [N]		[ <b>827]</b> 2700 K CRI 80	<b>[0-10V]</b> 0-10V	[HM2] Dark gray
		[ <b>740]</b> 4000 K CRI 70		[HM3] Anthracite gray
Narrow - NEMA Type 2 - 26°		[ <b>840</b> ] 4000 K CRI 80		[HM4] Light gray
[M] Medium - NEMA Type 4 - 60°				[HM5] White
				[HM6] Bronze
				[CC] Custom color (Please specify RAL code)
Extras	Accessories (To be ordered separately)			
Luminaire body	Optical accessories			
<b>[DPC]</b> Double powder coating	[ <b>100708017</b> ] Visor for VEGA			
	Mounting accessories			
	<b>[160405040]</b> Spike			