


VEGA

LF8021.695-US-S-700-830









[S] Spot - NEMA Type 0

Configuration

Light distribution	[S] 7°
Delivered lumens flux	3397 lm
Rated input power	35 W
Color temperature	3000 K CRI 80
Luminaire efficacy	84 lm/W
Lamp	4 LED
Color Deviation	5 SDCM
Lifetime L90 (hour)	>72,600
Lifetime L80 (hour)	>72,600

Options

Technical information

Mounting	Yoke mount (standard), stake mount (optional)
Tilt angle	+60°/-30°
Housing	Corrosion resistant, die-cast, marine grade
	aluminum housing
Finishing	Chromate conversion pretreatment followed by
	electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Liquid silicone
Lens / Reflector	High reflectance aluminium coating [S] [N],
	PMMA lens with high optical efficiency [MN] [M]
Glass / Diffusor	Tempered safety glass
Impact protection	IK07
Ingress protection	IP65
Input voltage	120-277V 50/60Hz
Insulation class	Class I
Wind catching area	0.40 ft ²
(EPA)	
Weight	14.3 lbs
LEB	M 1: 1: 1: 1 150

Multi-chip high power LEDs on metal-core PCB **LED** module Driver Internal LED driver **Driver surge** 10/6 kV

protection **Power factor** > 0.95 Through wiring Single power cord entry

-40...50°C Operating

temperature

Power cord 16" of flexible power cord

We reserve the right to change specifications without prior

written notice. Edition: 06.05.2024. For current version visit

heperlighting.com. All flux (±%7 tolerance) and power values

(±%10 tolerance) are derived following appropriate IES, CIE,

and applicable standards.

Accessories (To be ordered separately)

Optical accessories

Mounting accessories





Visor for VEGA

Spike 160405040

Project na	me		Туре	Quantity	
Date		Note			

LF8021.695-US-S-700-830-__-

Light distribution	Rated input power	Color temperature	Control	Product colors
[S] Spot - NEMA Type 0 -	[700] 35 W	[830] 3000 K CRI 80	[ONOFF] On/Off	[HM1] Black
7° [N] Narrow - NEMA Type 2 - 26°		[827] 2700 K CRI 80	[0-10V] 0-10V	[HM2] Dark gray
		[740] 4000 K CRI 70		[HM3] Anthracite gray
[MN] Medium narrow - NEMA Type 3 - 42°		[840] 4000 K CRI 80		[HM4] Light gray
[M] Medium - NEMA Type 4 - 60°				[HM5] White
				[HM6] Bronze
				[CC] Custom color (Pleas specify RAL code)
Extras	Accessories (To be ordered separately)			
Luminaire body	Optical accessories			
[DPC] Double powder coating	[100708017] Visor for VEGA			
	Mounting accessories			
	[160405040] Spike			