
VEGAS


IK07 IP65



LF8020.693-US-N-700-830-UNI-C1









Narrow

Variant

Light distribution [N] 26° Delivered lumens flux 849 lm Rated input power 10 W **Colour temperature** 3000 K CRI 80 **Luminaire efficacy** 84 lm/W Lamp 1 LED MacAdam Ellipse 5 SDCM >72,600 Lifetime L90B50 (hour) Lifetime L80B50 (hour) >72,600

Options

Gasket

Technical information

Mounting Surface mountable via a bracket (standard) or

spike (optional)

Tilt angle +60°/-30° Housing Corrosion resistant, die-cast, marine grade

aluminum housing

Finishing Chromate conversion pretreatment followed by

electrostatic powder coating **Fasteners** Stainless steel (AISI 304 / EN 1.4301 grade)

Liquid silicone

High reflectance aluminium coating [S] [N], Lens / Reflector

PMMA lens with high optical efficiency [MN] [M]

Tempered safety glass

Glass / Diffusor Impact protection **IK07**

Ingress protection IP65 Input voltage 120-277V 50/60Hz

Insulation class Class I

4.5 lbs Weight

Multi-chip high power LEDs on metal-core PCB **LED** module

Driver Internal LED driver

Driver surge 1/1 kV

protection

Power factor > 0.90 Through wiring Single cable entry

-30...50°C Operating

temperature

0.5 m of flexible cable Cable

Accessories (To be ordered separately)

Optical accessories

Mounting accessories





Visor for VEGA S

100708016

Spike 160405040

Project name					Туре	Quantity	
Date			Note				

LF8020.693-US-N-700-830-__-UNI-C1-__-

Light distribution	Rated input power	Colour temperature	Control	Product colours
[N] Narrow - 26°	[700] 10 W	[830] 3000 K CRI 80	[ONOFF] On/Off	[HM1] Black
[S] Spot - 7°		[827] 2700 K CRI 80	[0-10V] 0-10V	[HM2] Dark grey
[MN] Medium narrow - 42°		[740] 4000 K CRI 70		[HM3] Anthracite grey
[M] Medium - 60°		[840] 4000 K CRI 80		[HM4] Light grey
				[HM5] White
				[HM6] Bronze
				[CC] Custom colour (Pleas specify RAL code)
Extras	Accessories (To be ordered separately)			I
Luminaire body	Optical accessories			
options [DPC]	- [100708016] Visor for VEGA S			
Double powder coating	Mounting accessories			
	[160405040] Spike			